



Features

- Strictly limited to 500 microphones worldwide
- Custom spec 1" dual diaphragm capsule
- Vintage twin triode GE JAN-6072 valve
- Nine polar patterns
- Variable Pad & Filter

- Second 6072 valve in aluminium case
- Leather bound collector's book
- Machined from solid brass, hand-polished body
- Double-shielded oxygen-free 9m (30') cable
- Designed and manufactured in Australia
- Lifetime warranty*

Specifications

Acoustic Principle

Pressure, Pressure gradient

Directional Pattern

Shipping Weight

Switchable Omnidirectional / Cardioid / Figure-8 in nine steps

-37dB re 1V/Pa (14mV @ 94dB Sensitivity SPL) +/-2dB

Length - 201mm (7.9133") Dimensions

Diameter - 65mm (2.5590")

8.9kg

Frequency Range

Output Impedence

Output Connection

Net Weight

20 Hz-20 kHz


200Ω


3 pin XLR, balanced output between Pin 2 (+), Pin 3 (-)


and Pin 1 (ground)

1440g

Polar Pattern









Response Frequency







Included Accessories

- Transformer (variable polar/pad/filter)
- Aluminium case
- Second 6072 valve in aluminium cylinder
- RM2 (stand mount)
- SM2 (shock mount)
- Premium 30′/10m lead
- Leather bound collectors book
- Personalised titanium warranty card (redeemed via online registration)

www.rodemic.com