

# COMPRESSION DRIVERS



## PSD:2013

✓ SCREW-ON

✓ BOLT-ON

### SPECIFICATION

Throat Size	1.0", 25.4 mm
Nominal Impedance*	8 $\Omega$ (16 $\Omega$ available in bolt-on only)
Minimum Impedance	8.7 ohm @ 5.3 kHz
Power Rating*	85 W (AES)
Resonance	438 Hz
DC Resistance (Re)	6.80 $\Omega$
Usable Frequency Range	1.5 kHz - 20 kHz
Recommended Crossover	1.5 kHz / 12 dB
Sensitivity*	108.3 dB
Magnet Material	Ferrite
Magnet Weight	34 oz, 0.96 kg
Voice Coil Diameter	2.0", 51 mm
Voice Coil Former	Polymide
Diaphragm Material	Titanium

### MOUNTING INFORMATION

Overall Diameter	5.25", 133.4 mm
Driver Volume Displaced	0.018 cu. ft., 0.51 liters
Depth	2.30", 58.4 mm
Net Weight	5.60 lb, 2.5 kg
Shipping Weight	5.90 lb, 2.7 kg
Mounting Thread	1 3/8 in. 18 ext.
Mounting Holes Diameter	2X 1/4-20
Mounting Holes B.C.D.	3.00", 76.2 mm

### FREQUENCY RESPONSE & IMPEDANCE CURVE\*

