REDCOAT GUITAR SERIES

TONKERLITE[™]

A lightweight 12" guitar speaker with nice round, punchy, balanced tone like the Tonker, but a touch brighter on the top end and less lower-mid definition – ail at 4 lbs.!

12" 125 WATTS 8 Ω



SPECIFICATION

MOUNTING INFORMATION


Shipping Weight

MATERIALS OF CONSTRUCTION

Nominal Basket Diameter	12", 305 mm	Enclosure Type		Copper voice coil
Nominal Impedance*	8 Ω	Closed Back	Acceptable	Polyimide former
Power Rating*	125 W	Open Back	Acceptable	Neodymium magnet
Resonance (Fs)	109 Hz	Driver Volume Displaced	0.059 cu.ft., 1.67 liters	Non-vented core
Usable Frequency Range	80 Hz – 5 kHz	Overall Diameter	12.03", 305.6 mm	Pressed steel basket
Sensitivity*	101.1 dB	Baffle Hole Diameter	11.07", 281.2 mm	Paper cone
DC Resistance (Re)	7.2 Ω	Depth	5.1", 129.5 mm	Paper cone edge
Qts	0.8	Front Sealing Gasket	Yes	Zurette dust cap
Magnet Weight	4 oz.	Rear Sealing Gasket	Yes	-
Gap Height	0.28", 7.1 mm	Mounting Holes Diameter	0.25", 6.4 mm	
Voice Coil Diameter	2", 51 mm	Mounting Holes B.C.D.	11.59", 294.4 mm	
		Net Weight	4.1 lbs , 1.86 kg	

5.8 lbs , 2.63 kg

FREQUENCY RESPONSE & IMPEDANCE CURVE*







See footnotes on page 155 for information regarding usable frequency range, nominal impedance, power rating and sensitivity.