


## 54LS13/DM74LS13 Dual 4-Input Schmitt Trigger

### General Description

This device contains two independent gates each of which perform the logic NAND function. Each input has hysteresis which increases the noise immunity and transforms a slowly changing input signal to a fast changing jitter free output.

### Connection Diagram



TL/F/10166-1

Order Number 54LS13DMQB, 54LS13FMQB,  
54LS13LMQB, DM74LS13M or DM74LS13N  
See NS Package Number E20A,  
J14A, M14A, N14A or W14B

## Absolute Maximum Ratings (Note)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage	7V
Input Voltage	7V
Operating Free Air Temperature Range	
54LS	-55°C to +125°C
DM74LS	0°C to +70°C
Storage Temperature Range	-65°C to +150°C

Note: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

## Recommended Operating Conditions

Symbol	Parameter	54LS13			DM74LS13			Units
		Min	Nom	Max	Min	Nom	Max	
V <sub>CC</sub>	Supply Voltage	4.5	5	5.5	4.75	5	5.25	V
V <sub>IH</sub>	High Level Input Voltage	2			2			V
V <sub>IL</sub>	Low Level Input Voltage			0.7			0.8	V
I <sub>OH</sub>	High Level Output Current			-0.4			-0.4	mA
I <sub>OL</sub>	Low Level Output Current			4			8	mA
T <sub>A</sub>	Free Air Operating Temperature	-55		125	0		70	°C

## Electrical Characteristics

 over recommended operating free air temperature range (unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ (Note 1)	Max	Units
V <sub>I</sub>	Input Clamp Voltage	V <sub>CC</sub> = Min, I <sub>I</sub> = -18 mA				-1.5	V
V <sub>OH</sub>	High Level Output Voltage	V <sub>CC</sub> = Min, I <sub>OH</sub> = Max,		54LS	2.5		V
		V <sub>IL</sub> = Max		DM74	2.7		
V <sub>OL</sub>	Low Level Output Voltage	V <sub>CC</sub> = Min, I <sub>OL</sub> = Max,		54LS		0.4	V
		V <sub>IH</sub> = Min		DM74		0.5	
		I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = Min		DM74		0.4	
I <sub>I</sub>	Input Current @ Max Input Voltage	V <sub>CC</sub> = Max, V <sub>I</sub> = 10V				0.1	mA
I <sub>IH</sub>	High Level Input Current	V <sub>CC</sub> = Max, V <sub>I</sub> = 2.7V				20	μA
I <sub>IL</sub>	Low Level Input Current	V <sub>CC</sub> = Max, V <sub>I</sub> = 0.4V				-0.4	mA
I <sub>OS</sub>	Short Circuit Output Current	V <sub>CC</sub> = Max (Note 2)	54LS	-20		-100	mA
			DM74	-20		-100	
I <sub>CCH</sub>	Supply Current with Outputs High	V <sub>CC</sub> = Max V <sub>IN</sub> = GND				6.0	mA
I <sub>CCL</sub>	Supply Current with Outputs Low	V <sub>CC</sub> = Max V <sub>IN</sub> = OPEN				7.0	mA
V <sub>T+</sub>	Positive-Going Threshold Voltage	V <sub>CC</sub> = +5.0V		1.5		2.0	V
V <sub>T-</sub>	Negative-Going Threshold Voltage	V <sub>CC</sub> = +5.0V		0.6		1.1	V
V <sub>T+ - VT-</sub>	Hysteresis Voltage	V <sub>CC</sub> = +5.0V		0.4			V
I <sub>T+</sub>	Input Current at Positive-Going Threshold	V <sub>CC</sub> = +5.0V, V <sub>IN</sub> = V <sub>T+</sub>		-0.14*			mA
I <sub>T-</sub>	Input Current at Negative-Going Threshold	V <sub>CC</sub> = +5.0V, V <sub>IN</sub> = V <sub>T-</sub>		-0.18*			mA

\*Typical Value

Note 1: All typicals are at V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C.

Note 2: Not more than one output should be shorted at a time, and the duration should not exceed one second.

**Switching Characteristics** $V_{CC} = +5.0V$ ,  $T_A = +25^\circ C$  (See Section 1 for test waveforms and output load)

Symbol	Parameter	$R_L = 2\text{ k}\Omega$ , $C_L = 15\text{ pF}$				Units	
		54LS		DM74			
		Min	Max	Min	Max		
$t_{PLH}$	Propagation Delay Time Low to High Level Output		22		25	ns	
$t_{PHL}$	Propagation Delay Time High to Low Level Output		27		30	ns	