



DIONICS, INC.

65 Rushmore Street
Westbury, NY 11590

Phone: (516) 997-7474

Fax: (516) 997-7479

Website: www.dionics-usa.com

LEVEL-SHIFTED GAS DISCHARGE DISPLAY DIGIT DRIVERS

DI-505B

DI-510B


General Description:

The DIONICS DI-505B and DI-510B series circuits are designed for interfacing between MOS or TTL circuitry and gas discharge display panels. Each section of these devices is made up of a switched constant current level shifter-capable of high voltage operation and a PNP-NPN driver transistor pair. The constant current operation of the level shifter stage results in low power dissipation. Input circuitry is suitable for open drain PMOS, CMOS, open-collector or standard TTL.

Features:



- ✓ 200V Level Shift Capability
- ✓ MOS and TTL Compatibility
- ✓ 6- and 8-line Versions
- ✓ Low Power Dissipation
- ✓ Reliable Dielectric Isolation Process

Circuit Schematic
(Each Section)







Package Layout:

DI-505B



DI-510B



Absolute Maximum Rating ($T_a = 25^{\circ}\text{C}$)

Characteristic	Symbol	Notes	Limits	Units
Supply Voltage	V_+	Measured With Respect to GND	200	V
Input Voltage	V_{in}	Measured With Respect to GND	35	V
Output Voltage	V_{out}	Measured With Respect to V_+ Terminal	90	V
Output Current	I_{out}		40	mA
Power Dissipation DI-510B	P_D	Derate at 8 mW/ $^{\circ}\text{C}$ Above 25°C Ambient	800	mW
DI-505B	P_D	Derate at 6 mW/ $^{\circ}\text{C}$ Above 25°C Ambient	600	mW
Storage Temperature	T_s		-55 to +125	$^{\circ}\text{C}$
Operating Temperature	T_o		0 to +70	$^{\circ}\text{C}$

Electrical Characteristics ($T_a = 25^{\circ}\text{C}$)

Parameter	Symbol	Notes	Conditions	Typ.	Max.	Units
Output Saturation Voltage	V_{out} (SAT)	$V_+ = 180\text{V}$; Measured With Respect to V_+ Terminal	$I_o = 25\text{mA}$; $V_i = 2.4\text{V}$	3	10	V
Output Leakage Current	I_{out} (OFF)	$V_+ = 180\text{V}$	$V_o = 90\text{V}$; $V_i = 0.4\text{V}$	0.1	10	μA
Input Current	I_{in} (ON)		$V_i = 2.4\text{V}$	340	400	μA
Supply Current	I_+	One Input at 2.4V, Others at 0.4V	$V_+ = 180\text{V}$; $V_i = 2.4\text{ V}$; $I_o = 0$	0.5	1.5	mA

Typical Application:

