

### PROGRAMMABLE SHUNT REGULATOR


The KA336-5.0/B integrated circuits are precision 5.0V shunt regulators. The monolithic IC voltage references operate as a low temperature coefficient 5.0V zener with 0.6ohm dynamic impedance. A third terminal on the KA336-5.0/B allow the reference voltage and temperature coefficient to be trimmed easily.

The KA336-5.0/B are useful as a precision 5.0V low voltage references it convenient in obtaining a stable reference from low voltage supplies. Further, since the KA336-5.0/B operate as shunt regulators, they can be used as either a positive or negative voltage reference. The KA236 is characterized for operation from - 25°C to 85°C. and the KA336 from 0°C to 70°C.

### FEATURES

- Low temperature coefficient
- Adjustable 4V to 6V
- Wide operating range current of 400  $\mu$ A to 10mA
- Three lead transistor package (TO-92)
- 0.6 ohm dynamic impedance
- $\pm 1.0\%$  initial tolerance available
- Guaranteed temperature stability
- Easily trimmed for minimum temperature drift
- Fast turn on

TO-92




1:ADJ, 2: +, 3: -

### ORDERING INFORMATION

Device	Package	Operating Temperature
KA336-5.0		0 ~ 70°C
KA336-5.0B	TO-92	
KA236-5.0		-25 ~ +85°C

### SCHEMATIC DIAGRAM



**ABSOLUTE MAXIMUM RATINGS**


Characteristic	Symbol	Value		Unit	
Reverse Current	$I_R$	15		mA	
Forward current	$I_F$	10		mA	
Operating Temperature Range KA336-5.0/B KA236-5.0	$T_{OPR}$	0 ~ +70 -25 ~ +85		°C	
Storage Temperature Range	$T_{STG}$	-60 ~ +150		°C	

**ELECTRICAL CHARACTERISTICS**(T<sub>MIN</sub> ≤ T<sub>A</sub> ≤ T<sub>MAX</sub> unless otherwise specified)

Characteristic	Symbol	Test Conditions	KA336/236			KA336B			Unit
			Min	Typ	Max	Min	Typ	Max	
Reverse Breakdown Voltage	$V_R$	T <sub>A</sub> = 25°C, $I_R$ = 1mA	4.8	5.0	5.2	4.9	5.0	5.1	V
Reverse Breakdown Change with Current	$\Delta V_R / \Delta I_R$	T <sub>A</sub> = 25°C 600 μA ≤ $I_R$ ≤ 10mA	—	6	20	—	6	20	mV
Reverse Dynamic Impedance	$Z_D$	T <sub>A</sub> = 25°C, $I_R$ = 1mA	—	0.6	2	—	0.6	2	Ω
Temperature Stability	$ST_T$	$I_R$ = 1mA T <sub>MIN</sub> ≤ T <sub>A</sub> ≤ T <sub>MAX</sub>	—	4	12	—	4	12	mV
Reverse Breakdown Change with Current	$\Delta V_R / \Delta I_R$	600 μA ≤ $I_R$ ≤ 10mA T <sub>MIN</sub> ≤ T <sub>A</sub> ≤ T <sub>MAX</sub>	—	6	24	—	6	24	mV
Reverse Dynamic Impedance	$Z_D$	$I_R$ = 1mA T <sub>MIN</sub> ≤ T <sub>A</sub> ≤ T <sub>MAX</sub>	—	0.8	2.5	—	0.8	2.5	Ω
Long Term Stability	ST	$I_R$ = 1mA T <sub>MIN</sub> ≤ T <sub>A</sub> ≤ T <sub>MAX</sub>	—	20	—	—	20	—	ppm

\* KA236: T<sub>MIN</sub> = -25°C, T<sub>MAX</sub> = 85°CKA336: T<sub>MIN</sub> = 0°C, T<sub>MAX</sub> = 70°C**TYPICAL PERFORMANCE CHARACTERISTICS**

Fig. 1 REVERSE VOLTAGE CHANGE



## TYPICAL PERFORMANCE CHARACTERISTICS

Fig. 2 REVERSE CHARACTERISTICS




Fig. 3 TEMPERATURE DRIFT






Fig. 4 FORWARD CHARACTERISTICS



# TO-92

Dimensions in Millimeters



SAMSUNG ELECTRONICS CO.,LTD.