

SNVS407B - DECEMBER 2005 - REVISED MARCH 2008

LM2717-ADJ Dual Step-Down DC/DC Converter

Check for Samples: LM2717-ADJ

FEATURES

DESCRIPTION

- Adjustable Buck Converter with a 2.2A, 0.16Ω , Internal Switch (Buck 1)
- Adjustable Buck Converter with a 3.2A, 0.16Ω , • Internal Switch (Buck 2)
- **Operating Input Voltage Range of 4V to 20V** •
- Input Undervoltage Protection
- 300kHz to 600kHz Pin Adjustable Operating • Frequency
- **Over Temperature Protection**
- Small 24-Lead TSSOP Package

APPLICATIONS

- **TFT-LCD** Displays
- **Handheld Devices**
- **Portable Applications**
- Laptop Computers
- **Automotive Applications**

The LM2717-ADJ is composed of two PWM DC/DC buck (step-down) converters. Both converters are used to generate an adjustable output voltage as low as 1.267V. Both also feature low R_{DSON} (0.16 Ω) internal switches for maximum efficiency. Operating frequency can be adjusted anywhere between 300kHz and 600kHz allowing the use of small external components. External soft-start pins for each converter enables the user to tailor the soft-start times to a specific application. Each converter may also be shut down independently with its own shutdown pin. The LM2717-ADJ is available in a low profile 24-lead TSSOP package ensuring a low profile overall solution.

AA

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet. All trademarks are the property of their respective owners.

SNVS407B – DECEMBER 2005 – REVISED MARCH 2008



www.ti.com

Typical Application Circuit



Connection Diagram

1 —	PGND	SW1	24				
2 —	PGND	V _{IN}	23				
3 —	AGND	CB1	22				
4 —	FB1	SHDN 1	21				
5 —	V _{C1}	SS 1	20				
6 —	V _{BG}	FSLCT	19				
7 —	V _{C2}	SS2	— 18				
8 —	FB2	SHDN2	17				
9 —	AGND	CB2	16				
10 —	AGND	V _{IN}	15				
11 —	PGND	V _{IN}	14				
12 —	PGND	SW2	— 13				
TSSOP 24 Package							

Figure 1. 24-Lead TSSOP Top View



LM2717-ADJ

www.ti.com

SNVS407B-DECEMBER 2005-REVISED MARCH 2008

Pin	Name	Function
1	PGND	Power ground. PGND and AGND pins must be connected together directly at the part.
2	PGND	Power ground. PGND and AGND pins must be connected together directly at the part.
3	AGND	Analog ground. PGND and AGND pins must be connected together directly at the part.
4	FB1	Buck 1 output voltage feedback input.
5	V _{C1}	Buck 1 compensation network connection. Connected to the output of the voltage error amplifier.
6	V _{BG}	Bandgap connection.
7	V _{C2}	Buck 2 compensation network connection. Connected to the output of the voltage error amplifier.
8	FB2	Buck 2 output voltage feedback input.
9	AGND	Analog ground. PGND and AGND pins must be connected together directly at the part.
10	AGND	Analog ground. PGND and AGND pins must be connected together directly at the part.
11	PGND	Power ground. PGND and AGND pins must be connected together directly at the part.
12	PGND	Power ground. PGND and AGND pins must be connected together directly at the part.
13	SW2	Buck 2 power switch input. Switch connected between V_{IN} pins and SW2 pin.
14	V _{IN}	Analog power input. All V_{IN} pins are internally connected and should be connected together directly at the part.
15	V _{IN}	Analog power input. All V_{IN} pins are internally connected and should be connected together directly at the part.
16	CB2	Buck 2 converter bootstrap capacitor connection.
17	SHDN2	Shutdown pin for Buck 2 converter. Active low.
18	SS2	Buck 2 soft start pin.
19	FSLCT	Switching frequency select input. Use a resistor to set the frequency anywhere between 300kHz and 600kHz.
20	SS1	Buck 1 soft start pin.
21	SHDN1	Shutdown pin for Buck 1 converter. Active low.
22	CB1	Buck 1 converter bootstrap capacitor connection.
23	V _{IN}	Analog power input. All V_{IN} pins are internally connected and should be connected together directly at the part.
24	SW1	Buck 1 power switch input. Switch connected between $V_{\mbox{\scriptsize IN}}$ pins and SW1 pin.

SNVS407B-DECEMBER 2005-REVISED MARCH 2008

TEXAS INSTRUMENTS

www.ti.com







SNVS407B-DECEMBER 2005-REVISED MARCH 2008



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

Absolute Maximum Ratings ⁽¹⁾

V _{IN}		-0.3V to 22V
SW1 Voltage		-0.3V to 22V
SW2 Voltage		-0.3V to 22V
FB1, FB2 Voltages		-0.3V to 7V
CB1, CB2 Voltages		-0.3V to V_{IN} +7V (V_{IN} = V_{SW})
V _{C1} Voltage		$1.75 \text{V} \leq \text{V}_{\text{C1}} \leq 2.25 \text{V}$
V _{C2} Voltage		$0.965V \le V_{C2} \le 1.565V$
SHDN1 Voltage		-0.3V to 7.5V
SHDN2 Voltage		-0.3V to 7.5V
SS1 Voltage		-0.3V to 2.1V
SS2 Voltage		-0.3V to 2.1V
FSLCT Voltage		AGND to 5V
Maximum Junction Temperature		150°C
Power Dissipation ⁽²⁾		Internally Limited
Lead Temperature		300°C
Vapor Phase (60 sec.)		215°C
Infrared (15 sec.)		220°C
ESD Susceptibility ⁽³⁾	Human Body Model	2kV

(1) Absolute maximum ratings are limits beyond which damage to the device may occur. Operating Ratings are conditions for which the device is intended to be functional, but device parameter specifications may not be guaranteed. For guaranteed specifications and test conditions, see the Electrical Characteristics table.

(2) The maximum allowable power dissipation is a function of the maximum junction temperature, $T_J(MAX)$, the junction-to-ambient thermal resistance, θ_{JA} , and the ambient temperature, T_A . See the Electrical Characteristics table for the thermal resistance. The maximum allowable power dissipation at any ambient temperature is calculated using: $P_D (MAX) = (T_{J(MAX)} - T_A)/\theta_{JA}$. Exceeding the maximum allowable power dissipation will cause excessive die temperature, and the regulator will go into thermal shutdown.

(3) The human body model is a 100 pF capacitor discharged through a $1.5k\Omega$ resistor into each pin.

Operating Conditions

Operating Junction Temperature Range	
	-40°C to +125°C
Storage Temperature	−65°C to +150°C
Supply Voltage	4V to 20V
SW1 Voltage	20V
SW2 Voltage	20V
Switching Frequency	300kHz to 600kHz

(1) All limits guaranteed at room temperature (standard typeface) and at temperature extremes (bold typeface). All room temperature limits are 100% tested or guaranteed through statistical analysis. All limits at temperature extremes are guaranteed via correlation using standard Statistical Quality Control (SQC) methods. All limits are used to calculate Average Outgoing Quality Level (AOQL).

SNVS407B-DECEMBER 2005-REVISED MARCH 2008

www.ti.com

Electrical Characteristics

Specifications in standard type face are for $T_J = 25^{\circ}$ C and those with **boldface type** apply over the full **Operating Temperature Range** ($T_J = -40^{\circ}$ C to +125°C). $V_{IN} = 5V$, $I_L = 0A$, and $F_{SW} = 300$ kHz unless otherwise specified.

Symbol	Parameter	Conditions	Min (1)	Тур (2)	Max (1)	Units
lo	Total Quiescent Current (both	Not Switching		2.7	6	mA
	switchers)	Switching, switch open		6	12	mA
		$V_{\overline{SHDN}} = 0V$		9	27	μA
V _{BG}	Bandgap Voltage		1.248 1.230	1.267	1.294 1.299	V
$%V_{BG}/\Delta V_{IN}$	Bandgap Voltage Line Regulation		-0.01		0.01 0.125	%/V
V _{FB1}	Buck 1 Feedback Voltage		1.236 1.214	1.258	1.286 1.288	V
V _{FB2}	Buck 2 Feedback Voltage		1.236 1.214	1.258	1.286 1.288	V
I _{CL1} ⁽³⁾	Buck 1 Switch Current Limit	$V_{IN} = 8V^{(4)}$		2.2		
		V _{IN} = 12V, V _{OUT} = 3.3V	1.4	1.65	2.0	A
I _{CL2} ⁽³⁾	Buck 2 Switch Current Limit	$V_{IN} = 8V^{(4)}$		3.2		•
		V _{IN} = 12V, V _{OUT} = 5V	2.6	3.05	3.5	A
I _{B1}	Buck 1 FB Pin Bias Current	V _{IN} = 20V		70	400	nA
I _{B2}	Buck 2 FB Pin Bias Current	V _{IN} = 20V		65	400	nA
V _{IN}	Input Voltage Range		4		20	V
g _{m1}	Buck 1 Error Amp Transconductance	$\Delta I = 20 \mu A$		1340		µmho
g _{m2}	Buck 2 Error Amp Transconductance	$\Delta I = 20 \mu A$		1360		µmho
A _{V1}	Buck 1 Error Amp Voltage Gain			134		V/V
A _{V2}	Buck 2 Error Amp Voltage Gain			136		V/V
D _{MAX}	Maximum Duty Cycle		89	93		%
F _{SW}	Switching Frequency	$R_F = 46.4k$	240	300	360	kHz
		R _F = 22.6k	480	600	720	kHz
I _{SHDN1}	Buck 1 Shutdown Pin Current	$0V < V_{\overline{SHDN1}} < 7.5V$	-5		5	μA
I _{SHDN2}	Buck 2 Shutdown Pin Current	$0V < V_{SHDN2} < 7.5V$	-5		5	μA
I _{L1}	Buck 1 Switch Leakage Current	V _{IN} = 20V		0.01	5	μA
I _{L2}	Buck 2 Switch Leakage Current	V _{IN} = 20V		0.01	5	μA
R _{DSON1}	Buck 1 Switch R _{DSON} ⁽⁶⁾	I _{SW} = 100mA		160	180 300	mΩ
R _{DSON2}	Buck 2 Switch R _{DSON} ⁽⁶⁾	I _{SW} = 100mA		160	180 300	mΩ
Th _{SHDN1}	Buck 1 SHDN Threshold	Output High	1.8	1.36		
		Output Low		1.33	0.7	V

(1) All limits guaranteed at room temperature (standard typeface) and at temperature extremes (bold typeface). All room temperature limits are 100% tested or guaranteed through statistical analysis. All limits at temperature extremes are guaranteed via correlation using standard Statistical Quality Control (SQC) methods. All limits are used to calculate Average Outgoing Quality Level (AOQL).

(2) Typical numbers are at 25°C and represent the most likely norm.

(3) Duty cycle affects current limit due to ramp generator.

(4) Current limit at 0% duty cycle. See TYPICAL PERFORMANCE section for Switch Current Limit vs. Input Voltage.

(5) Bias current flows into FB pin.

(6) Includes the bond wires and package leads, R_{DSON} from V_{IN} pin(s) to SW pin.

6 Submit Documentation Feedback



SNVS407B - DECEMBER 2005 - REVISED MARCH 2008

www.ti.com

Electrical Characteristics (continued)

Specifications in standard type face are for $T_J = 25^{\circ}$ C and those with **boldface type** apply over the full **Operating Temperature Range** ($T_J = -40^{\circ}$ C to $+125^{\circ}$ C). $V_{IN} = 5V$, $I_L = 0A$, and $F_{SW} = 300$ kHz unless otherwise specified.

Symbol	Parameter	Conditions	Min (1)	Тур (2)	Max (1)	Units	
Th _{SHDN2}	Buck 2 SHDN Threshold	Output High	1.8	1.36		N/	
		Output Low		1.33	0.7	V	
I _{SS1}	Buck 1 Soft Start Pin Current		4	9	15	μA	
I _{SS2}	Buck 2 Soft Start Pin Current		4	9	15	μA	
UVP	On Threshold		4	3.8		V	
C	Off Threshold			3.6	3.3	v	
θ_{JA}	Thermal Resistance	TSSOP, package only		115		°C/W	

(7) Refer to the www.ti.com/packaging for more detailed thermal information and mounting techniques for the TSSOP package.

SNVS407B - DECEMBER 2005 - REVISED MARCH 2008

Figure 2.



















STRUMENTS

EXAS

Typical Performance Characteristics

8

LM2717-ADJ





www.ti.com









Buck 1 Switch Current Limit vs. Temperature(V_{IN} = 12V)





Buck 2 Switch Current Limit vs. Input Voltage







SNVS407B-DECEMBER 2005-REVISED MARCH 2008



Switching Frequency vs. R_F Resistance





SNVS407B-DECEMBER 2005-REVISED MARCH 2008

BUCK OPERATION

PROTECTION (BOTH REGULATORS)

The LM2717-ADJ has dedicated protection circuitry running during normal operation to protect the IC. The Thermal Shutdown circuitry turns off the power devices when the die temperature reaches excessive levels. The UVP comparator protects the power devices during supply power startup and shutdown to prevent operation at voltages less than the minimum input voltage. The OVP comparator is used to prevent the output voltage from rising at no loads allowing full PWM operation over all load conditions. The LM2717-ADJ also features a shutdown mode for each converter decreasing the supply current to approximately 10µA (both in shutdown mode).

CONTINUOUS CONDUCTION MODE

The LM2717-ADJ contains current-mode, PWM buck regulators. A buck regulator steps the input voltage down to a lower output voltage. In continuous conduction mode (when the inductor current never reaches zero at steady state), the buck regulator operates in two cycles. The power switch is connected between V_{IN} and SW1 and SW2.

In the first cycle of operation the transistor is closed and the diode is reverse biased. Energy is collected in the inductor and the load current is supplied by C_{OUT} and the rising current through the inductor.

During the second cycle the transistor is open and the diode is forward biased due to the fact that the inductor current cannot instantaneously change direction. The energy stored in the inductor is transferred to the load and output capacitor.

The ratio of these two cycles determines the output voltage. The output voltage is defined approximately as:

$$D = \frac{V_{OUT}}{V_{IN}} , D' = (1-D)$$

where

- where D is the duty cycle of the switch
 - D and D' will be required for design calculation

The LM2717-ADJ has a minimum switch ON time which corresponds to a minimum duty cycle of approximately 10% at 600kHz operation and approximately 5% at 300kHz operation. In the case of some high voltage differential applications (low duty cycle operation) this minimum duty cycle may be exceeded causing the feedback pin over-voltage protection to trip as the output voltage rises. This will put the device into a PFM type operation which can cause an unpredictable frequency spectrum and may cause the average output voltage to rise slightly. If this is a concern the switching frequency may be lowered and/or a pre-load added to the output to keep the device full PWM operation. Note that the OVP function monitors the FB pin so it will not function if the feedback resistor is disconnected from the output. Due to slight differences between the two converters it is recommended that Buck 1 be used for the lower of the two output voltages for best operation.

DESIGN PROCEDURE

This section presents guidelines for selecting external components.

SETTING THE OUTPUT VOLTAGE

The output voltage is set using the feedback pin and a resistor divider connected to the output as shown in Figure 20. The feedback pin voltage (V_{FB}) is 1.258V, so the ratio of the feedback resistors sets the output voltage according to the following equation:

$$R_{FB1(3)} = R_{FB2(4)} x \frac{V_{OUT} - V_{FB1(2)}}{V_{FB1(2)}} \Omega$$

(2)

(1)

INPUT CAPACITOR

SNVS407B - DECEMBER 2005 - REVISED MARCH 2008

 $I_{RMS} = I_{OUT} \times \frac{\sqrt{V_{OUT}(V_{IN} - V_{OUT})}}{V_{IN}}$

should be at least 25% higher than the maximum input voltage. If a tantalum capacitor is used, the voltage rating required is about twice the maximum input voltage. The tantalum capacitor should be surge current tested by the manufacturer to prevent being shorted by the inrush current. The minimum capacitor value should be 47µF for lower output load current applications and less dynamic (quickly changing) load conditions. For higher output current applications or dynamic load conditions a 68µF to 100µF low ESR capacitor is recommended. It is also recommended to put a small ceramic capacitor (0.1µF to 4.7µF) between the input pins and ground to reduce high frequency spikes.

The RMS current reaches its maximum (I_{OUT}/2) when V_{IN} equals 2V_{OUT}. This value should be calculated for both regulators and added to give a total RMS current rating. For an aluminum or ceramic capacitor, the voltage rating

A low ESR aluminum, tantalum, or ceramic capacitor is needed between the input pin and power ground. This capacitor prevents large voltage transients from appearing at the input. The capacitor is selected based on the

INDUCTOR SELECTION

The most critical parameter for the inductor in a current mode switcher is the minimum value required for stable operation. To prevent subharmonic oscillations and achieve good phase margin a target minimum value for the inductor is:

$$L_{MIN} = \frac{(D-0.5+2/\pi)(V_{IN}-V_{OUT})R_{DSON}}{(1-D)(0.164*F_{SW})}$$
(H)

RMS current and voltage requirements. The RMS current is given by:

Where V_{IN} is the minimum input voltage and R_{DSON} is the maximum switch ON resistance. For best stability the inductor should be in the range of 0.5L_{MIN} (absolute minimum) and 2L_{MIN}. Using an inductor with a value less than 0.5L_{MIN} can cause subharmonic oscillations. The inductor should meet this minimum requirement at the peak inductor current expected for the application regardless of what the inductor ripple current and output ripple voltage requirements are. A value larger than 2L_{MIN} is acceptable if the ripple requirements of the application require it but it may reduce the phase margin and increase the difficulty in compensating the circuit.

The most important parameters for the inductor from an applications standpoint are the inductance, peak current and the DC resistance. The inductance is related to the peak-to-peak inductor ripple current, the input and the output voltages (for 300kHz operation):

$$L = \frac{(V_{IN} - V_{OUT})V_{OUT}}{V_{IN} \times I_{RIPPLE} \times 300 \text{ kHz}}$$
(5)

A higher value of ripple current reduces inductance, but increases the conductance loss, core loss, and current stress for the inductor and switch devices. It also requires a bigger output capacitor for the same output voltage ripple requirement. A reasonable value is setting the ripple current to be 30% of the DC output current. Since the ripple current increases with the input voltage, the maximum input voltage is always used to determine the inductance. The DC resistance of the inductor is a key parameter for the efficiency. Lower DC resistance is available with a bigger winding area. A good tradeoff between the efficiency and the core size is letting the inductor copper loss equal 2% of the output power.

OUTPUT CAPACITOR

The selection of C_{OUT} is driven by the maximum allowable output voltage ripple. The output ripple in the constant frequency, PWM mode is approximated by:

$$V_{\text{RIPPLE}} = I_{\text{RIPPLE}} \left(\text{ESR} + \frac{1}{8F_{\text{S}}C_{\text{OUT}}} \right)$$

The ESR term usually plays the dominant role in determining the voltage ripple. Low ESR ceramic, aluminum electrolytic, or tantalum capacitors (such as MuRata MLCC, Taiyo Yuden MLCC, Nichicon PL series, Sanyo OS-CON, Sprague 593D, 594D, AVX TPS, and CDE polymer aluminum) is recommended. An aluminum electrolytic capacitor is not recommended for temperatures below -25°C since its ESR rises dramatically at cold temperatures. Ceramic or tantalum capacitors have much better ESR specifications at cold temperature and is preferred for low temperature applications.

(4)

(6)

Copyright © 2005–2008, Texas Instruments Incorporated

ISTRUMENTS



BOOTSTRAP CAPACITOR

A 4.7nF ceramic capacitor or larger is recommended for the bootstrap capacitor. For applications where the input voltage is less than twice the output voltage a larger capacitor is recommended, generally 0.1μ F to 1μ F to ensure plenty of gate drive for the internal switches and a consistently low R_{DSON}.

SOFT-START CAPACITOR (BOTH REGULATORS)

The LM2717-ADJ contains circuitry that can be used to limit the inrush current on start-up of the DC/DC switching regulators. This inrush current limiting circuitry serves as a soft-start. The external SS pins are used to tailor the soft-start for a specific application. A current (I_{SS}) charges the external soft-start capacitor, C_{SS} . The soft-start time can be estimated as:

$$\Gamma_{\rm SS} = C_{\rm SS}^* 0.6 \text{V/I}_{\rm SS}$$

(7)

When programming the soft-start time use the equation given in the *Soft-Start Capacitor* section above. The softstart function is used simply to limit inrush current to the device that could stress the input voltage supply. The soft-start time described above is the time it takes for the current limit to ramp to maximum value. When this function is used the current limit starts at a low value and increases to nominal at the set soft-start time. Under maximum load conditions the output voltage may rise at the same rate as the soft-start, however at light or no load conditions the output voltage will rise much faster as the switch will not need to conduct much current to charge the output capacitor.

SHUTDOWN OPERATION (BOTH REGULATORS)

The shutdown pins of the LM2717-ADJ are designed so that they may be controlled using 1.8V or higher logic signals. If the shutdown function is not to be used the pin may be left open. The maximum voltage to the shutdown pin should not exceed 7.5V. If the use of a higher voltage is desired due to system or other constraints it may be used, however a 100k or larger resistor is recommended between the applied voltage and the shutdown pin to protect the device.

SCHOTTKY DIODE

The breakdown voltage rating of D_1 and D_2 is preferred to be 25% higher than the maximum input voltage. The current rating for the diode should be equal to the maximum output current for best reliability in most applications. In cases where the input voltage is much greater than the output voltage the average diode current is lower. In this case it is possible to use a diode with a lower average current rating, approximately $(1-D)*I_{OUT}$ however the peak current rating should be higher than the maximum load current.

LOOP COMPENSATION

The general purpose of loop compensation is to meet static and dynamic performance requirements while maintaining stability. Loop gain is what is usually checked to determine small-signal performance. Loop gain is equal to the product of control-output transfer function and the output-control transfer function (the compensation network transfer function). The DC loop gain of the LM2717 is usually around 55dB to 60dB when loaded. Generally speaking it is a good idea to have a loop gain slope that is -20dB /decade from a very low frequency to well beyond the crossover frequency. The crossover frequency should not exceed one-fifth of the switching frequency, i.e. 60kHz in the case of 300kHz switching frequency. The higher the bandwidth is, the faster the load transient response speed will potentially be. However, if the duty cycle saturates during a load transient, further increasing the small signal bandwidth will not help. Since the control-output transfer function usually has very limited low frequency gain, it is a good idea to place a pole in the compensation at zero frequency, so that the low frequency gain will be relatively large. A large DC gain means high DC regulation accuracy (i.e. DC voltage changes little with load or line variations). The rest of the compensation scheme depends highly on the shape of the control-output plot.

As shown in Figure 17, the example control-output transfer function consists of one pole (fp), one zero (fz), and a double pole at fn (half the switching frequency). The following can be done to create a -20dB /decade roll-off of the loop gain: Place the first pole at 0Hz, the first zero at fp, the second pole at fz, and the second zero at fn. The resulting output-control transfer function is shown in Figure 18.

STRUMENTS





Figure 17. Control-Output Transfer Function

The control-output corner frequencies, and thus the desired compensation corner frequencies, can be determined approximately by the following equations:

$$f_z = \frac{1}{2\pi R_e C_o}$$

where

- C_o is the output capacitance
- R_e is the output capacitance ESR
- f is the switching frequency

$$f_{p} = \frac{1}{2\pi R_{o}C_{o}} + \frac{.5}{2\pi L f C_{o}}$$

where

- C_o is the output capacitance
- R_o is the load resistance
- f is the switching frequency

Since fp is determined by the output network, it will shift with loading (Ro) and duty cycle. First determine the range of frequencies (fpmin/max) of the pole across the expected load range, then place the first compensation zero within that range.

Example: V_o = 5V, R_e = 20m Ω , C_o = 100 μ F, R_{omax} = 5V/100mA = 50 Ω , R_{omin} = 5V/1A = 5 Ω , L = 10 μ H, f = 300kHz:

$$f_{z} = \frac{1}{2\pi \cdot 20 \text{ m}\Omega \cdot 100 \text{ }\mu\text{F}} = 80 \text{ }\text{kHz}$$
(10)
$$f_{p \text{ min}} = \frac{1}{2\pi \cdot 50\Omega \cdot 100 \text{ }\mu\text{F}} + \frac{0.5}{2\pi \cdot 300 \text{ }\text{k} \cdot 10\mu \cdot 100 \text{ }\mu\text{F}} = 297 \text{ }\text{Hz}$$
(11)

$$f_{p \max} = \frac{1}{2\pi \cdot 5\Omega \cdot 100 \ \mu\text{F}} + \frac{0.5}{2\pi \cdot 300\text{k} \cdot 10\mu \cdot 100 \ \mu\text{F}} = 584 \ \text{Hz}$$
(12)

Once the fp range is determined, R_{c1} should be calculated using:

Figure 18. Output-Control Transfer Function

(8)

(9)



$$R_{c1} = \frac{B}{gm} \left(\frac{R_1 + R_2}{R_1} \right)$$

where

- B is the desired gain in V/V at fp (fz1)
- gm is the transconductance of the error amplifier
- 1 and R2 are the feedback resistors as shown in Figure 19 ٠

A gain value around 10dB (3.3v/v) is generally a good starting point.

Example: B = 3.3 v/v, gm= 1350μ mho, R1 = $20 \text{ K}\Omega$, R2 = $59 \text{ K}\Omega$:

$$R_{c1} = \frac{3.3}{1350\mu} \cdot \frac{20k + 59k}{20k} \approx 9.76k$$
(14)

Bandwidth will vary proportional to the value of Rc1. Next, Cc1 can be determined with the following equation:

$$C_{c1} = \frac{1}{2\pi \cdot f_{p} \cdot R_{c1}}$$
(15)

Example: fpmin = 297 Hz, Rc1 = 20 K Ω :

$$C_{c1} = \frac{1}{2\pi \cdot 297 \text{ Hz} \cdot 9.76 \text{k}} \approx 56 \text{ nF}$$
(16)

The value of C_{c1} should be within the range determined by fpmin/max. A higher value will generally provide a more stable loop, but too high a value will slow the transient response time.

The compensation network (Figure 19) will also introduce a low frequency pole which will be close to 0Hz.

A second pole should also be placed at fz. This pole can be created with a single capacitor Cc2 and a shorted Rc2 (see Figure 19). The minimum value for this capacitor can be calculated by:

$$C_{c2 \min} = \frac{1}{2\pi \cdot f_z \cdot R_{c1}}$$
(17)

Cc2 may not be necessary, however it does create a more stable control loop. This is especially important with high load currents.

Example:
$$fz = 80 \text{ kHz}$$
, $Rc1 = 20 \text{ K}\Omega$:
 $C_{c2 \text{ min}} = \frac{1}{2\pi \cdot 80 \text{ kHz} \cdot 20 \text{ k}\Omega} \simeq 100 \text{ pF}$
(18)

A second zero can also be added with a resistor in series with Cc2. If used, this zero should be placed at fn, where the control to output gain rolls off at -40dB/dec. Generally, fn will be well below the 0dB level and thus will have little effect on stability. Rc2 can be calculated with the following equation:

$$R_{c2} = \frac{1}{2\pi \cdot f_{n} \cdot C_{c2}}$$

$$(19)$$

$$\frac{\hat{V}_{c}}{\hat{V}_{c1}} = \hat{V}_{a}$$

$$R_{2}$$

Figure 19. Compensation Network

network



(13)

SNVS407B - DECEMBER 2005 - REVISED MARCH 2008

TEXAS INSTRUMENTS

www.ti.com

Note that the values calculated here give a good baseline for stability and will work well with most applications. The values in some cases may need to be adjusted some for optimum stability or the values may need to be adjusted depending on a particular applications bandwidth requirements.

LAYOUT CONSIDERATIONS

The LM2717-ADJ uses two separate ground connections, PGND for the drivers and boost NMOS power device and AGND for the sensitive analog control circuitry. The AGND and PGND pins should be tied directly together at the package. The feedback and compensation networks should be connected directly to a dedicated analog ground plane and this ground plane must connect to the AGND pin. If no analog ground plane is available then the ground connections of the feedback and compensation networks must tie directly to the AGND pin. Connecting these networks to the PGND can inject noise into the system and effect performance.

The input bypass capacitor C_{IN} , as shown in Figure 20, must be placed close to the IC. This will reduce copper trace resistance which effects input voltage ripple of the IC. For additional input voltage filtering, a 0.1μ F to 4.7μ F bypass capacitors can be placed in parallel with C_{IN} , close to the V_{IN} pins to shunt any high frequency noise to ground. The output capacitors, C_{OUT1} and C_{OUT2} , should also be placed close to the IC. Any copper trace connections for the C_{OUTX} capacitors can increase the series resistance, which directly effects output voltage ripple. The feedback network, resistors $R_{FB1(3)}$ and $R_{FB2(4)}$, should be kept close to the FB pin, and away from the inductor to minimize copper trace connections that can inject noise into the system. Trace connections made to the inductors and schottky diodes should be minimized to reduce power dissipation and increase overall efficiency. For more detail on switching power supply layout considerations see Application Note AN-1149: *Layout Guidelines for Switching Power Supplies* (SNVA021).

APPLICATION INFORMATION

Manufacturer	Inductor	Contact Information
Coilcraft	DO3316 and DT3316 series	www.coilcraft.com 800-3222645
TDK	SLF10145 series	www.component.tdk.com 847-803-6100
Pulse	P0751 and P0762 series	www.pulseeng.com
Sumida	CDRH8D28 and CDRH8D43 series	www.sumida.com

Table 1. Some Recommended Inductors (Others May Be Used)

Table 2. Some Recommended Input And Output Capacitors (Others May Be Used)

Manufacturer	Capacitor	Contact Information		
Vishay Sprague	293D, 592D, and 595D series tantalum	www.vishay.com		
Taiyo Yuden	High capacitance MLCC ceramic	www.t-yuden.com		
Cornell Dubilier	ESRD seriec Polymer Aluminum Electrolytic SPV and AFK series V-chip series	www.cde.com		
MuRata	High capacitance MLCC ceramic	www.murata.com		



SNVS407B-DECEMBER 2005-REVISED MARCH 2008









SNVS407B – DECEMBER 2005 – REVISED MARCH 2008



Figure 22. 3.3V, 1.8V Output Application



www.ti.com

PACKAGING INFORMATION

Orderable Device	Status	Package Type	Package	Pins	Package Qty	Eco Plan	Lead/Ball Finish	MSL Peak Temp	Op Temp (°C)	Top-Side Markings	Samples
	(1)		Drawing			(2)		(3)		(4)	
LM2717MT-ADJ	ACTIVE	TSSOP	PW	24	61	TBD	Call TI	Call TI	-40 to 125	LM2717 MT-ADJ	Samples
LM2717MT-ADJ/NOPB	ACTIVE	TSSOP	PW	24	61	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	LM2717 MT-ADJ	Samples
LM2717MTX-ADJ	ACTIVE	TSSOP	PW	24	2500	TBD	Call TI	Call TI	-40 to 125	LM2717 MT-ADJ	Samples
LM2717MTX-ADJ/NOPB	ACTIVE	TSSOP	PW	24	2500	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	LM2717 MT-ADJ	Samples

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ Only one of markings shown within the brackets will appear on the physical device.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.





9-Mar-2013

PACKAGE MATERIALS INFORMATION

www.ti.com

Texas Instruments

TAPE AND REEL INFORMATION





QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal												
Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
LM2717MTX-ADJ	TSSOP	PW	24	2500	330.0	16.4	6.95	8.3	1.6	8.0	16.0	Q1
LM2717MTX-ADJ/NOPB	TSSOP	PW	24	2500	330.0	16.4	6.95	8.3	1.6	8.0	16.0	Q1

TEXAS INSTRUMENTS

www.ti.com

PACKAGE MATERIALS INFORMATION

17-Nov-2012



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
LM2717MTX-ADJ	TSSOP	PW	24	2500	349.0	337.0	45.0
LM2717MTX-ADJ/NOPB	TSSOP	PW	24	2500	349.0	337.0	45.0

PW (R-PDSO-G24)

PLASTIC SMALL OUTLINE



NOTES:

A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
B. This drawing is subject to change without notice.

Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.

Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.

E. Falls within JEDEC MO-153



IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have *not* been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products		Applications	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	TI E2E Community	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2013, Texas Instruments Incorporated