



DUAL 2-TO-4 LINE DECODER/DEMUTIPLEXER

- HIGH SPEED
 $t_{PD} = 16 \text{ ns (TYP.)}$ at $V_{CC} = 5V$
- LOW POWER DISSIPATION
 $I_{CC} = 4 \mu\text{A}$ (MAX.) at $T_A = 25^\circ\text{C}$
- HIGH NOISE IMMUNITY
 $V_{NIH} = V_{NIL} = 28\% V_{CC}$ (MIN.)
- OUTPUT DRIVE CAPABILITY
 10 LSTTL LOADS
- SYMMETRICAL OUTPUT IMPEDANCE
 $|I_{OH}| = |I_{OL}| = 4 \text{ mA (MIN.)}$
- BALANCED PROPAGATION DELAYS
 $t_{PLH} = t_{PHL}$
- WIDE OPERATING VOLTAGE RANGE
 V_{CC} (OPR) = 2V to 6V
- PIN AND FUNCTION COMPATIBLE
 WITH 54/74LS139



DESCRIPTION

The M54/74HC139 is a high speed CMOS DUAL TWO LINE TO FOUR LINE DECODER/DEMUL- TIPLEXER fabricated in silicon gate C²MOS technology. It has the same high speed performance of LSTTL combined with true CMOS low power consumption. The active low enable input can be used for gating or as a data input for demultiplexing applications. While the enable input is held high, all four outputs are high independently of the other inputs. All inputs are equipped with protection circuits against static discharge and transient excess voltage.

INPUT AND OUTPUT EQUIVALENT CIRCUIT



PIN CONNECTIONS (top view)




NC =
 No Internal
 Connection

TRUTH TABLE

INPUTS			OUTPUTS				SELECTED OUTPUT	
ENABLE	SELECT		\bar{Y}_0	\bar{Y}_1	\bar{Y}_2	\bar{Y}_3		
\bar{G}	B	A						
H	X	X	H	H	H	H	NONE	
L	L	L	L	H	H	H	\bar{Y}_0	
L	L	H	H	L	H	H	\bar{Y}_1	
L	H	L	H	H	L	H	\bar{Y}_2	
L	H	H	H	H	H	L	\bar{Y}_3	

X: DON'T CARE

LOGIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CC}	Supply Voltage	- 0.5 to 7	V
V_I	DC Input Voltage	- 0.5 to $V_{CC} + 0.5$	V
V_O	DC Output Voltage	- 0.5 to $V_{CC} + 0.5$	V
I_{IK}	DC Input Diode Current	± 20	mA
I_{OK}	DC Output Diode Current	± 20	mA
I_O	DC Output Source Sink Current Per Output Pin	± 25	mA
I_{CC} or I_{GND}	DC V_{CC} or Ground Current	± 50	mA
P_D	Power Dissipation	500 (*)	mW
Tstg	Storage Temperature	- 65 to 150	°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied.

(*) 500 mW: $\equiv 65^\circ\text{C}$ derate to 300 mW by 10 mW/ $^\circ\text{C}$: 65°C to 85°C

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Value		Unit
V_{CC}	Supply Voltage	2 to 6		V
V_I	Input Voltage	0 to V_{CC}		V
V_O	Output Voltage	0 to V_{CC}		V
T_A	Operating Temperature 74HC Series 54HC Series	- 40 to 85 - 55 to 125		°C
t_r, t_f	Input Rise and Fall Time	V_{CC} { 2 V 4.5V 6 V	0 to 1000 0 to 500 0 to 400	ns

DC SPECIFICATIONS

Symbol	Parameter	V_{CC}	Test Condition	T _A = 25°C 54HC and 74HC			- 40 to 85°C 74HC		- 55 to 125°C 54HC		Unit
				Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
V_{IH}	High Level Input Voltage	2.0		1.5	—	—	1.5	—	1.5	—	V
		4.5		3.15	—	—	3.15	—	3.15	—	
		6.0		4.2	—	—	4.2	—	4.2	—	
V_{IL}	Low Level Input Voltage	2.0		—	—	0.5	—	0.5	—	0.5	V
		4.5		—	—	1.35	—	1.35	—	1.35	
		6.0		—	—	1.8	—	1.8	—	1.8	
V_{OH}	High Level Output Voltage	2.0		V_I	I_O	1.9	2.0	—	1.9	—	V
		4.5		V_{IH} or V_{IL}	- 20 μ A	4.4	4.5	—	4.4	—	
		6.0				5.9	6.0	—	5.9	—	
		4.5		V_{IL}	- 4.0 mA	4.18	4.31	—	4.13	—	
		6.0			- 5.2 mA	5.68	5.8	—	5.63	—	
V_{OL}	Low Level Output Voltage	2.0		V_{IH} or V_{IL}	20 μ A	—	0	0.1	—	0.1	V
		4.5				—	0	0.1	—	0.1	
		6.0				—	0	0.1	—	0.1	
		4.5		V_{IL}	4.0 mA	—	0.17	0.26	—	0.33	—
		6.0			5.2 mA	—	0.18	0.26	—	0.33	—
I_I	Input Leakage Current	6.0	$V_I = V_{CC}$ or GND	—	—	± 0.1	—	± 1	—	± 1	μ A
I_{CC}	Quiescent Supply Current	6.0	$V_I = V_{CC}$ or GND	—	—	4	—	40	—	80	μ A

AC ELECTRICAL CHARACTERISTICS ($V_{CC} = 5V$, $T_A = 25^\circ C$, $C_L = 15pF$, Input $t_r = t_f = 6ns$)

Symbol	Parameter	54HC and 74HC			Unit
		Min.	Typ.	Max.	
t_{TLH} t_{THL}	Output Transition Time		4	8	ns
t_{PLH} t_{PHL}	Propagation Delay Time		16	26	ns
t_{PLH} t_{PHL}	Propagation Delay Time (G-Y)		14	23	ns

AC ELECTRICAL CHARACTERISTICS ($C_L = 50\text{pF}$, Input $t_r = t_f = 6\text{ns}$)


Symbol	Parameter	V_{CC}	Test Condition	$T_A = 25^\circ\text{C}$ 54HC and 74HC			- 40 to 85°C 74HC		- 55 to 125°C 54HC		Unit
				Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
t_{TLH} t_{THL}	Output Transition Time	2.0		—	30	75	—	95	—	110	ns
		4.5		—	8	15	—	19	—	22	
		6.0		—	7	13	—	16	—	19	
t_{PLH} t_{PHL}	Propagation Delay Time A, B-Y	2.0		—	76	150	—	190	—	225	ns
		4.5		—	19	30	—	38	—	45	
		6.0		—	17	26	—	33	—	38	
t_{PLH} t_{PHL}	Propagation Delay Time G-Y	2.0		—	68	135	—	170	—	205	ns
		4.5		—	17	27	—	34	—	41	
		6.0		—	15	23	—	29	—	35	
C_{IN}	Input Capacitance			—	5	10	—	10	—	—	pF
$C_{PD} (*)$	Power Dissipation Capacitance			—	49	—	—	—	—	—	pF

Note (*) C_{PD} is defined as the value the IC's of internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit)

Average operating current can be obtained by the following equation.

$$I_{CC(\text{opr})} = C_{PD} \cdot V_{CC} \cdot I_{IN} + I_{CC}$$

SWITCHING CHARACTERISTICS TEST CIRCUIT

TEST CIRCUIT I_{CC} (Opr.)