


QUAD 2-INPUT "OR" GATE


MC3100/MC3000 series

MC3103F • MC3003F
MC3103L • MC3003L,P

CIRCUIT SCHEMATIC
 1/4 OF CIRCUIT SHOWN




This device consists of four 2-input OR gates. This non-inverting function is useful for optimizing logic design, or for direct implementation of standard logic equations.



Positive Logic: $3 = 1 + 2$
 Negative Logic: $3 = 1 \cdot 2$


Input Loading Factor = 1
 Output Loading Factor = 10
 Total Power Dissipation = 150 mW typ/pkg
 Propagation Delay Time = 9.0 ns typ

SWITCHING TIME TEST CIRCUIT AND WAVEFORMS




$C_T = 25 \text{ pF}$ = total parasitic capacitance, which includes probe, wiring, and load capacitances.

The coax delays from input to scope and output to scope must be matched. The scope must be terminated in 50-ohm impedance. The 950-ohm resistor and the scope termination impedance constitute a 20:1 attenuator probe. Coax shall be CT-070-50 or equivalent.



ELECTRICAL CHARACTERISTICS

Test procedures are shown for only one gate. The other gates are tested in the same manner. Further, test procedures are shown for only one input of the gate under test. To complete testing, sequence through remaining inputs.



TEST CURRENT/VOLTAGE VALUES																					
			mA			Volts															
			I _{OL}	I _{OH}	I _{in}	I _b	V _{IL}	V _{IH}	V _F	V _E	V _{RH}	V _{max}	V _{CC}	V _{CCL}	V _{CH}						
MC3003	Temperature	-55°C	20	-2.0	-	-	1.1	2.0	0.4	2.4	4.0	-	5.0	4.5	5.5						
		+25°C	20	-2.0	-10	1.1	1.8	0.4	2.4	4.0	7.0	5.0	4.5	5.5							
		+125°C	20	-2.0	-	-	0.8	1.8	0.4	2.4	4.0	-	5.0	4.5	5.5						
		0°C	20	-2.0	-	-	1.1	2.0	0.4	2.5	4.0	-	5.0	4.75	5.25						
		+25°C	20	-2.0	-10	1.1	1.8	0.4	2.5	4.0	7.0	5.0	4.75	5.25							
MC3003	+75°C	20	-2.0	-	-	0.8	1.8	0.4	2.5	4.0	-	5.0	4.75	5.25							
TEST CURRENT / VOLTAGE APPLIED TO PINS LISTED BELOW:																					
Characteristic	Symbol	Pin Under Test	MC3003 Test Limits																		
			-55°C		+25°C		0°C		+25°C		+75°C										
Input	Characteristic	Symbol	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Unit								
			I _F	1	-	-2.0	-	-2.0	-	-2.0	-	-2.0	mAdc	I _{OL}	I _{OH}	I _{in}	I _b				
			I _R	1	-	50	-	50	-	50	-	50	μAdc								
			BV _{in}	1	-	5.5	-	-	-	5.5	-	-	Vdc								
			V _D	1	-	-	-	-	-	-1.5	-	-	Vdc								
Output	Characteristic	Symbol																			
			V _{OL}	3	-	0.4	-	0.4	-	0.4	-	0.4	Vdc	I _{OL}	I _{OH}	V _F	V _E				
			V _{OH}	3	2.4	-	2.4	-	2.5	-	2.5	-	Vdc								
			I _{SC}	3	-40	-100	-40	-100	-40	-100	-40	-100	mAdc								
Short-Circuit Current	Characteristic	Symbol																			
Power Requirements (Total Device)	Characteristic	Symbol																			
Switching Parameters	Characteristic	Symbol																			
Turn-On Delay	t _{pd}	1,3	-	-	-	15	-	-	-	15	-	-	14	-	-	7					
		1,3	-	-	-	12	-	-	-	12	-	-	14	-	-	7					

Since this is a non-inverting gate, power drain is minimized by tying the inputs to gates not under test to V_{RH}