


8-INPUT "NAND" GATE


MCBC5400/MCB5400F series

MCBC5430*
MCB5430F*



This device is an 8-input NAND gate. It is useful when processing a large number of variables, such as in encoders and decoders.

Beam lead sealed junction technology is used to manufacture these devices. They are particularly useful in highly reliable systems using hybrid beam lead assembly techniques or standard flat package assembly techniques.




Positive Logic:
 $12 = 2 \cdot 3 \cdot 5 \cdot 6 \cdot 7 \cdot 8 \cdot 9 \cdot 10$

Negative Logic:
 $12 = 2 + 3 + 5 + 6 + 7 + 8 + 9 + 10$

Input Loading Factor = 1
Output Loading Factor = 10
Total Power Dissipation = 10 mW typ/pkg
Propagation Delay Time = 10 ns typ


SWITCHING TIME TEST CIRCUIT AND WAVEFORMS



*F suffix = 1/4" x 1/4" ceramic package (Case 651). MCBC-prefixed devices are unencapsulated. Beam numbers are the same as the pin numbers for flat-packaged devices. See General Information section for package and chip details.

ELECTRICAL CHARACTERISTICS

Test procedures are shown for only one input. To complete testing, sequence through remaining inputs in the same manner.



			TEST CURRENT /VOLTAGE VALUES (All Temperatures)												
			Volts												
			mA		V _{IL}	V _{IH}	V _{IHH}	V _{RI}	V _{R2}	V _{h1}	V _{h0}	V _{CC}	V _{CCL}	V _{CCH}	
			I _{OL}	I _{OH}	-0.4	0.4	2.4	5.5	4.5	5.0	2.0	0.8	5.0	4.50	5.50
			16												
TEST CURRENT /VOLTAGE APPLIED TO PINS LISTED BELOW :															
Characteristic	Symbol	Pin Under Test	Test Limits		V _{IL}	V _{IH}	V _{IHH}	V _{RI}	V _{R2}	V _{h1}	V _{h0}	V _{CC}	V _{CCL}	V _{CCH}	
			Min	Max											Unit
Input	Forward Current	I _F	2	-	-1.6	mAdc	-	2	-	3,5,6,7,8,9,10	-	-	-	4	
Leakage Current	I _{RI}	2	-	40	μAdc	-	-	-	-	-	-	-	-	4	
	I _{R2}	2	-	1.0	mAdc	-	-	-	-	-	-	-	-	4	
Output	Output Voltage	V _{OL}	12	-	0.4	Vdc	-	-	-	2,3,5,6,7,8,9,10	-	4	-	11	
	V _{OH}	12	2.4	-	Vdc	-	-	3,5,6,7,8,9,10	-	-	2	-	4	-	11
	I _{SC}	12	-20	-55	mAdc	-	-	-	-	-	-	-	-	4	2,3,5,6,7,8,9,10,11,12
Power Requirements															
Power Supply Drain	I _{PDH}	4	-	6.0	mAdc	-	-	-	2,3,5,6,7,8,9,10	-	-	-	-	4	11
Switching Parameters	I _{PDL}	4	-	2.0	mAdc	-	-	-	-	-	-	-	-	4	2,3,5,6,7,8,9,10,11
Turn-On Delay	t _{pd-}	2,12	-	15**	ns	-	3,5,6,7,8,9,10	-	-	-	-	4	-	-	11
Turn-Off Delay	t _{pd+}	2,12	-	22**	ns	-	3,5,6,7,8,9,10	-	-	-	-	4	-	-	11

***Tested only at 25°C.