



The Infinite Bandwidth Company™

# MIC7211/7221

## IttyBitty™ Rail-to-Rail Input Comparator

### Final Information

### General Description

The MIC7211 and MIC7221 are micropower comparators featuring rail-to-rail input performance in Micrel's IttyBitty™ SOT-23-5 package. The MIC7211/21 is ideal for systems where small size is a critical consideration.

The MIC7211/21 is optimized for single supply operation from 2.2V to 10V power supplies.

The MIC7211 features a conventional push-pull output while the MIC7221 has an open-drain output for mixed-voltage applications with an external pull-up resistor.

The MIC7211/21 benefits small battery-operated portable electronic devices where small size and the ability to place the comparator close to the signal source are primary design concerns.

### Features

- Small footprint SOT-23-5 package
- Guaranteed performance at 2.2V, 2.7V, 5V, and 10V
- 7µA typical supply current at 5V
- <5µs response time at 5V
- Push-pull output (MIC7211)
- Open-drain output (MIC7221)
- Input voltage range may exceed supply voltage by 0.3V
- >100mA typical sink or source


### Applications

- Battery-powered products
- Notebook computers and PDAs
- PCMCIA cards
- Cellular and other wireless communication devices
- Alarm and security circuits
- Direct sensor interface


### Ordering Information

Part Number	Temp. Range	Package	Mark
MIC7211BM5	-40°C to +85°C	SOT-23-5	A14
MIC7221BM5	-40°C to +85°C	SOT-23-5	A15

### Pin Configuration



### Functional Configuration



SOT-23-5 (M5)

### Pin Description

Pin Number	Pin Name	Pin Function
1	OUT	Amplifier Output
2	V+	Positive Supply
3	IN+	Noninverting Input
4	IN-	Inverting Input
5	V-	Negative Supply

**Absolute Maximum Ratings (Note 1)**

Supply Voltage ( $V_{V+} - V_{V-}$ )	12V
Differential Input Voltage ( $V_{IN+}, V_{IN-}$ )	$\pm(V_{V+} - V_{V-})$
I/O Pin Voltage ( $V_{IN+}, V_{OUT}$ ), <b>Note 3</b>	$V_{V+} + 0.3V$ to $V_{V-} - 0.3V$
Junction Temperature ( $T_J$ )	+150°C
Storage Temperature ( $T_S$ )	-65°C to +150°C

ESD, **Note 6**

**Operating Ratings (Note 2)**

Supply Voltage ( $V_{V+} - V_{V-}$ )	2.2V to 10V
Junction Temperature ( $T_J$ )	-40°C to +85°C
Maximum Junction Temperature ( $T_{J(max)}$ ) <b>Note 4</b>	+125°C
Package Thermal Resistance ( $\theta_{JA}$ ) <b>Note 5</b>	325°C/W
Maximum Power Dissipation	<b>Note 4</b>

**DC Electrical Characteristics (2.2V)**

$V_{V+} = +2.2V$ ,  $V_{V-} = 0V$ ,  $V_{CM} = V_{OUT} = V_{V+}/2$ ;  $T_J = 25^\circ C$ , **bold** values indicate  $-40^\circ C \leq T_J \leq +85^\circ C$ ; **Note 7**; unless noted

Symbol	Parameter	Condition	Min	Typ	Max	Units
$V_{OS}$	Input Offset Voltage			2	10	mV
$TCV_{OS}$	Input Offset Voltage Temperature Drift			1		$\mu V/^\circ C$
$TCV_{OS}$	Input Offset Voltage Drift Over Time			3.3		$\mu V/month$
$I_B$	Input Bias Current			0.5		pA
$I_{OS}$	Input Offset Current			0.25		pA
CMRR	Common-Mode Rejection Ratio	$0V \leq V_{CM} \leq 2.2V$		60		dB
PSRR	Positive Power Supply Rejection Ratio	$V_{V+} = 2.2V$ to 5V		90		dB
$A_{VOL}$	Gain			125		dB
$V_{OH}$	Output Voltage (High)	MIC7211, $I_{LOAD} = 2.5mA$	2.1	2.18		V
$V_{OL}$	Output Voltage (Low)	$I_{LOAD} = 2.5mA$		0.02	0.1	V
$I_S$	Supply Current	$V_{OUT} = low$		5	12	$\mu A$

**DC Electrical Characteristics (2.7V)**

$V_{V+} = +2.7V$ ,  $V_{V-} = 0V$ ,  $V_{CM} = V_{OUT} = V_{V+}/2$ ;  $T_J = 25^\circ C$ , **bold** values indicate  $-40^\circ C \leq T_J \leq +85^\circ C$ ; **Note 7**; unless noted

Symbol	Parameter	Condition	Min	Typ	Max	Units
$V_{OS}$	Input Offset Voltage			2	10	mV
$TCV_{OS}$	Input Offset Voltage Temperature Drift			1		$\mu V/^\circ C$
$TCV_{OS}$	Input Offset Voltage Drift Over Time			3.3		$\mu V/month$
$I_B$	Input Bias Current			0.5		pA
$I_{OS}$	Input Offset Current			0.25		pA
CMRR	Common-Mode Rejection Ratio	$0V \leq V_{CM} \leq 2.7V$		65		dB
PSRR	Positive Power Supply Rejection Ratio	$V_{V+} = 2.7V$ to 5V		90		dB
$A_{VOL}$	Gain			125		dB
$V_{OH}$	Output Voltage (High)	MIC7211, $I_{LOAD} = 2.5mA$	2.6	2.68		V
$V_{OL}$	Output Voltage (Low)	$I_{LOAD} = 2.5mA$		0.02	0.1	V
$I_S$	Supply Current	$V_{OUT} = low$		5	12	$\mu A$

**DC Electrical Characteristics (5V)**

$V_{V+} = +5.0V$ ,  $V_{V-} = 0V$ ,  $V_{CM} = V_{OUT} = V_{V+}/2$ ;  $T_J = 25^\circ C$ , **bold** values indicate  $-40^\circ C \leq T_J \leq +85^\circ C$ ; **Note 7**; unless noted

Symbol	Parameter	Condition	Min	Typ	Max	Units
$V_{OS}$	Input Offset Voltage			2	10	mV
$TCV_{OS}$	Input Offset Voltage Temperature Drift			1		$\mu V/^\circ C$
$TCV_{OS}$	Input Offset Voltage Drift Over Time			3.3		$\mu V/month$
$I_B$	Input Bias Current			0.5		pA
$I_{OS}$	Input Offset Current			0.25		pA
CMRR	Common-Mode Rejection Ratio	$0V \leq V_{CM} \leq 5.0V$		70		dB
PSRR	Positive Power Supply Rejection Ratio	$V_{V+} = 5.0V$ to 10V		90		dB
$A_{VOL}$	Gain			125		dB
$V_{OH}$	Output Voltage (High)	MIC7211, $I_{LOAD} = 5mA$	4.9	4.95		V
$V_{OL}$	Output Voltage (Low)	$I_{LOAD} = 5mA$		0.05	0.1	V
$I_S$	Supply Current	$V_{OUT} = low$		7	14	$\mu A$
$I_{SC}$	Short Circuit Current	MIC7211, sourcing		150		mA
		sinking		110		mA

**DC Electrical Characteristics (10V)**

$V_{V+} = +10V$ ,  $V_{V-} = 0V$ ,  $V_{CM} = V_{OUT} = V_{V+}/2$ ;  $T_J = 25^\circ C$ , **bold** values indicate  $-40^\circ C \leq T_J \leq +85^\circ C$ ; **Note 7**; unless noted

Symbol	Parameter	Condition	Min	Typ	Max	Units
$V_{OS}$	Input Offset Voltage			2	10	mV
$TCV_{OS}$	Input Offset Voltage Temperature Drift			1		$\mu V/^\circ C$
$TCV_{OS}$	Input Offset Voltage Drift Over Time			3.3		$\mu V/month$
$I_B$	Input Bias Current			0.5		pA
$I_{OS}$	Input Offset Current			0.25		pA
CMRR	Common-Mode Rejection Ratio	$0V \leq V_{CM} \leq 10V$		75		dB
PSRR	Positive Power Supply Rejection Ratio	$V_{V+} = 5.0V$ to 10V		90		dB
$A_{VOL}$	Gain			125		dB
$V_{OH}$	Output Voltage (High)	MIC7211, $I_{LOAD} = 5mA$	9.9	9.95		V
$V_{OL}$	Output Voltage (Low)	$I_{LOAD} = 5mA$		0.05	0.1	V
$I_S$	Supply Current	$V_{OUT} = low$		12	25	$\mu A$
$I_{SC}$	Short Circuit Current	MIC7211, sourcing		165		mA
		sinking		125		mA

## AC Electrical Characteristics

$V_{V-} = 0V$ ,  $V_{CM} = V_{OUT} = V_{V+}/2$ ;  $T_J = 25^\circ C$ , **bold** values indicate  $-40^\circ C \leq T_J \leq +85^\circ C$ ; **Note 7**; unless noted

Symbol	Parameter	Condition	Min	Typ	Max	Units
$t_{RISE}$	Rise Time	$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		75		ns
$t_{FALL}$	Fall Time	$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		70		ns
$t_{PHL}$	Propagation Delay-High to Low	$V_{V+} = 2.2V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		10		$\mu s$
		$V_{V+} = 2.2V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 100mV, <b>Note 9</b>		6.0		$\mu s$
		$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		13		$\mu s$
		$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 100mV, <b>Note 9</b>		5		$\mu s$
$t_{PLH}$	Propagation Delay-Low to High	$V_{V+} = 2.2V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		13.5		$\mu s$
		$V_{V+} = 2.2V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 100mV, <b>Note 9</b>		4.0		$\mu s$
		$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 10mV, <b>Note 9</b>		11.5		$\mu s$
		$V_{V+} = 5.0V$ , $f = 10kHz$ , $C_{LOAD} = 50pF$ overdrive = 100mV, <b>Note 9</b>		3.0		$\mu s$

**Note 1.** Exceeding the absolute maximum rating may damage the device.

**Note 2.** The device is not guaranteed to function outside its operating rating.

**Note 3.** I/O pin voltage is any external voltage to which an input or output is referenced.

**Note 4.** The maximum allowable power dissipation is a function of the maximum junction temperature,  $T_{J(max)}$ ; the junction-to-ambient thermal resistance,  $\theta_{JA}$ ; and the ambient temperature,  $T_A$ . The maximum allowable power dissipation at any ambient temperature is calculated using  $P_{D(max)} = (T_{J(max)} - T_A) / \theta_{JA}$ . Exceeding the maximum allowable power dissipation will result in excessive die temperature.

**Note 5.** Thermal resistance,  $\theta_{JA}$ , applies to a part soldered on a printed circuit board.


**Note 6.** Devices are ESD sensitive. Handling precautions recommended.

**Note 7.** All limits guaranteed by testing on statistical analysis.


**Note 8.** Continuous short circuit may exceed absolute maximum  $T_J$  under some conditions.

**Note 9.** The MIC7221 requires 5k $\Omega$  pull-up resistor.

## Partial Functional Diagrams



**MIC7211 Push-Pull Output**



**MIC7221 Open-Drain Output**

## Application Information

The small outline and low supply current (typically  $7\mu\text{A}$  at  $5\text{V}$ ) of the MIC7211/21 are the primary advantages of these comparators. They have been characterized for  $2.2\text{V}$ ,  $2.7\text{V}$ ,  $5\text{V}$ , and  $10\text{V}$  operation.

Their  $2.2\text{V}$  capability is especially useful in low-battery voltage situations. Low-voltage operation allows longer battery life or deeper discharge capability. Even at  $2.2\text{V}$ , the output can drive several logic-gate inputs. At  $2.5\text{mA}$ , the output stage voltage drop is guaranteed to not exceed  $0.1\text{V}$ .

### Outputs

The MIC7211 has a push-pull output while the MIC7221 has an open-drain output, otherwise both comparators share a common design.

The open-drain MIC7221 output can be pulled up to  $10\text{V}$ , even when the supply voltage is as low as  $2.2\text{V}$ . Conversely, the output also can be pulled up to voltages that are lower than the positive supply. Logic-level translation is readily facilitated by the ability to pull the open-drain output to voltages above or below the power supply.

Although specified short-circuit output current specified for these parts typically exceeds  $100\text{mA}$ , their output is not intended to sink or source anywhere near  $100\text{mA}$ . The short-circuit rating is only presented as additional information regarding output impedance and may be useful for determining the voltage drop one may experience when driving a given load.


### Input Bias Current

The low input-bias current (typically  $0.5\text{pA}$ ) requirement of the MIC7211/21 provides flexibility in the kinds of circuitry and devices that can be directly interfaced.

Designs using an amplifier for transducer-to-comparator impedance transformation may be simplified by using the MIC7211/21's low-input-current requirement to eliminate the amplifier.

### Input Signal Levels

Input signals may exceed either supply rail by up to  $0.2\text{V}$  without phase inversion or other adverse effects. The inputs have internal clamp diodes to the supply pins.



Note:  $R_F$  and  $R_1$  control hysteresis (typically,  $R_F \gg R_1$ ).


**Figure 1. Driving the Input Beyond the Supply Rails**

Larger input swings can be accommodated if the input current is limited to  $1\text{mA}$  or less. Using a  $100\text{k}$  input resistor will allow an input to swing up to  $100\text{V}$  beyond either supply rail. Because of the low input bias current of the device, even larger input resistors are practical. See Figure 1. The ability

to swing the input beyond either rail facilitates some otherwise difficult circuits, such as a single-supply zero-crossing detector or a circuit that senses its own supply voltage.

The comparator must be powered if an input is pulled above the rail, even with current limiting in effect. Figure 2 shows a hypothetical situation where an input is pulled higher than the rail when the power supply is off or not present. Figure 2 also shows external clamp diodes for additional input circuit protection. Discrete clamp diodes can be arbitrarily more robust than the internal clamp diodes.

The power supply has been simplified (real power supplies do not have a series output diode); however, this illustrates a common characteristic of most positive-voltage power supplies: they are designed to source, but not sink, current. If the supply is off, or disconnected, there is no limiting voltage for the clamp diode to reference. The input signal can charge the the bypass capacitor, and possibly the filter capacitor, up to the applied input ( $V_{IN}$ ). This may be high enough to cause a thin-oxide rupture in a CMOS integrated circuit.



Note:  $1\text{V} \leq V^{++} \leq 10\text{V}$

**Figure 2. Avoid This Condition**

Ideally, the supply for the comparator and the input-producing circuitry should be the same or be switched simultaneously.

### Bypass Capacitors



CMOS circuits, especially logic gates with their totem-pole (push-pull) output stages, generate power supply current spikes (noise) on the supply and/or ground lines. These spikes occur because, for a finite time during switching, both output transistors are partially on allowing "shoot-through current." Bypass capacitors reduce this noise.

Adequate bypassing for the MIC7211 comparator is  $0.01\mu\text{F}$ ; in low-noise systems, where this noise may interfere with the functioning or accuracy of nearby circuitry,  $0.1\mu\text{F}$  is recommended. Because the MIC7221 does not have a totem-pole output stage, this spiking is not evident; however, switching a capacitive load can present a similar situation.

### Thermal Behavior

The thermal impedance of a SOT-23-5 package is  $325^\circ\text{C}/\text{W}$ . The  $5\text{V}$  Electrical Characteristics table shows a maximum voltage drop of  $0.1\text{V}$  for a  $5\text{mA}$  output current, making the output resistance about  $20\Omega$  ( $R = 0.1/0.005 = 20\Omega$ ). Attempting to draw the typical specified output short-circuit current of  $150\text{mA}$  (sourcing) can be expected to cause a die temperature rise of  $146^\circ\text{C}$ . (Operating die temperature for ICs should generally not exceed  $125^\circ\text{C}$ .) Using a series resistance is the simplest form of protecting against damage by excessive output current.

### Package Information



**SOT-23-5 (M5)**



---

**MICREL INC. 1849 FORTUNE DRIVE SAN JOSE, CA 95131 USA**

TEL + 1 (408) 944-0800 FAX + 1 (408) 944-0970 WEB <http://www.micrel.com>

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 1999 Micrel Incorporated