

# MM54C00/MM74C00 Quad 2-Input NAND Gate MM54C02/MM74C02 Quad 2-Input NOR Gate MM54C04/MM74C04 Hex Inverter MM54C10/MM74C10 Triple 3-Input NAND Gate MM54C20/MM74C20 Dual 4-Input NAND Gate

## General Description

These logic gates employ complementary MOS (CMOS) to achieve wide power supply operating range, low power consumption, high noise immunity and symmetric controlled rise and fall times. With features such as this the 54C/74C logic family is close to ideal for use in digital systems. Function and pin out compatibility with series 54/74 devices minimizes design time for those designers already familiar with the standard 54/74 logic family.


All inputs are protected from damage due to static discharge by diode clamps to  $V_{CC}$  and GND.

## Features


- Wide supply voltage range 3.0V to 15V
- Guaranteed noise margin 1.0V
- High noise immunity 0.45  $V_{CC}$  (typ.)
- Low power consumption 10 nW/package (typ.)
- Low power TTL compatibility fan out of 2 driving 74L

## Connection Diagrams


MM54C00/MM74C00




MM54C02/MM74C02




MM54C04/MM74C04



MM54C10/MM74C10



MM54C20/MM74C20



## Absolute Maximum Ratings

|                                          |                          |
|------------------------------------------|--------------------------|
| Voltage at Any Pin                       | -0.3V to $V_{CC} + 0.3V$ |
| Operating Temperature Range              |                          |
| 54C                                      | -55°C to +125°C          |
| 74C                                      | -40°C to +85°C           |
| Storage Temperature Range                | -65°C to +150°C          |
| Operating $V_{CC}$ Range                 | 3.0V to 15V              |
| Maximum $V_{CC}$ Voltage                 | 18V                      |
| Package Dissipation                      | 500 mW                   |
| Lead Temperature (Soldering, 10 seconds) | 300°C                    |

## DC Electrical Characteristics

Min/max limits apply across the guaranteed temperature range unless otherwise noted.

| Parameter                                                                                   | Conditions                 | Min.                                                                            | Typ.                             | Max.       | Units   |
|---------------------------------------------------------------------------------------------|----------------------------|---------------------------------------------------------------------------------|----------------------------------|------------|---------|
| <b>CMOS to CMOS</b>                                                                         |                            |                                                                                 |                                  |            |         |
| $V_{IN(1)}$                                                                                 | Logical "1" Input Voltage  | $V_{CC} = 5.0V$<br>8.0                                                          |                                  |            | V       |
| $V_{IN(0)}$                                                                                 | Logical "0" Input Voltage  | $V_{CC} = 5.0V$<br>$V_{CC} = 10V$                                               |                                  | 1.5<br>2.0 | V       |
| $V_{OUT(1)}$                                                                                | Logical "1" Output Voltage | $V_{CC} = 5.0V, I_O = -10\mu A$<br>$V_{CC} = 10V, I_O = -10\mu A$               | 4.5<br>9.0                       |            | V       |
| $V_{OUT(0)}$                                                                                | Logical "0" Output Voltage | $V_{CC} = 5.0V, I_O = +10\mu A$<br>$V_{CC} = 10V, I_O = +10\mu A$               |                                  | 0.5<br>1.0 | V       |
| $I_{IN(1)}$                                                                                 | Logical "1" Input Current  | $V_{CC} = 15V, V_{IN} = 15V$                                                    | 0.005                            | 1.0        | $\mu A$ |
| $I_{IN(0)}$                                                                                 | Logical "0" Input Current  | $V_{CC} = 15V, V_{IN} = 0V$                                                     | -1.0                             | -0.005     | $\mu A$ |
| $I_{CC}$                                                                                    | Supply Current             | $V_{CC} = 15V$                                                                  | 0.01                             | 15         | $\mu A$ |
| <b>Low Power to CMOS</b>                                                                    |                            |                                                                                 |                                  |            |         |
| $V_{IN(1)}$                                                                                 | Logical "1" Input Voltage  | 54C, $V_{CC} = 4.5V$<br>74C, $V_{CC} = 4.75V$                                   | $V_{CC} - 1.5$<br>$V_{CC} - 1.5$ |            | V       |
| $V_{IN(0)}$                                                                                 | Logical "0" Input Voltage  | 54C, $V_{CC} = 4.5V$<br>74C, $V_{CC} = 4.75V$                                   |                                  | 0.8<br>0.8 | V       |
| $V_{OUT(1)}$                                                                                | Logical "1" Output Voltage | 54C, $V_{CC} = 4.5V, I_O = -10\mu A$<br>74C, $V_{CC} = 4.75V, I_O = -10\mu A$   | 4.4<br>4.4                       |            | V       |
| $V_{OUT(0)}$                                                                                | Logical "0" Output Voltage | 54C, $V_{CC} = 4.5V, I_O = +10\mu A$<br>74C, $V_{CC} = 4.75V, I_O = +10\mu A$   |                                  | 0.4<br>0.4 | V       |
| <b>CMOS to Low Power</b>                                                                    |                            |                                                                                 |                                  |            |         |
| $V_{IN(1)}$                                                                                 | Logical "1" Input Voltage  | 54C, $V_{CC} = 4.5V$<br>74C, $V_{CC} = 4.75V$                                   | 4.0<br>4.0                       |            | V       |
| $V_{IN(0)}$                                                                                 | Logical "0" Input Voltage  | 54C, $V_{CC} = 4.5V$<br>74C, $V_{CC} = 4.75V$                                   |                                  | 1.0<br>1.0 | V       |
| $V_{OUT(1)}$                                                                                | Logical "1" Output Voltage | 54C, $V_{CC} = 4.5V, I_O = -360\mu A$<br>74C, $V_{CC} = 4.75V, I_O = -360\mu A$ | 2.4<br>2.4                       |            | V       |
| $V_{OUT(0)}$                                                                                | Logical "0" Output Voltage | 54C, $V_{CC} = 4.5V, I_O = 360\mu A$<br>74C, $V_{CC} = 4.75V, I_O = 360\mu A$   |                                  | 0.4<br>0.4 | V       |
| <b>Output Drive (See 54C/74C Family Characteristics Data Sheet) (short circuit current)</b> |                            |                                                                                 |                                  |            |         |
| $I_{SOURCE}$                                                                                | Output Source Current      | $V_{CC} = 5.0V, V_{IN(0)} = 0V$<br>$T_A = 25^\circ C, V_{OUT} = 0V$             | -1.75                            |            | mA      |
| $I_{SOURCE}$                                                                                | Output Source Current      | $V_{CC} = 10V, V_{IN(0)} = 0V$<br>$T_A = 25^\circ C, V_{OUT} = 0V$              | -8.0                             |            | mA      |
| $I_{SINK}$                                                                                  | Output Sink Current        | $V_{CC} = 5.0V, V_{IN(1)} = 5.0V$<br>$T_A = 25^\circ C, V_{OUT} = V_{CC}$       | 1.75                             |            | mA      |
| $I_{SINK}$                                                                                  | Output Sink Current        | $V_{CC} = 10V, V_{IN(1)} = 10V$<br>$T_A = 25^\circ C, V_{OUT} = V_{CC}$         | 8.0                              |            | mA      |

# AC Electrical Characteristics

$T_A = 25^\circ\text{C}$ ,  $C_L = 50\text{ pF}$ , unless otherwise specified.

| Parameter                                                | Conditions                                                                                      | Min. | Typ.     | Max.      | Units    |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------------|------|----------|-----------|----------|
| <b>MM54C00/MM74C00, MM54C02/MM74C02, MM54C04/MM74C04</b> |                                                                                                 |      |          |           |          |
| $t_{pd0}$ , $t_{pd1}$                                    | Propagation Delay Time to Logical "1" or "0"<br>$V_{CC} = 5.0\text{V}$<br>$V_{CC} = 10\text{V}$ |      | 50<br>30 | 90<br>60  | ns<br>ns |
| $C_{IN}$                                                 | Input Capacitance<br>(Note 2)                                                                   |      | 6.0      |           | pF       |
| $C_{PD}$                                                 | Power Dissipation Capacitance<br>(Note 3) Per Gate or Inverter                                  |      | 12       |           | pF       |
| <b>MM54C10/MM74C10</b>                                   |                                                                                                 |      |          |           |          |
| $t_{pd0}$ , $t_{pd1}$                                    | Propagation Delay Time to Logical "1" or "0"<br>$V_{CC} = 5.0\text{V}$<br>$V_{CC} = 10\text{V}$ |      | 60<br>35 | 100<br>70 | ns<br>ns |
| $C_{IN}$                                                 | Input Capacitance<br>(Note 2)                                                                   |      | 7.0      |           | pF       |
| $C_{PD}$                                                 | Power Dissipation Capacitance<br>(Note 3) Per Gate                                              |      | 18       |           | pF       |
| <b>MM54C20/MM74C20</b>                                   |                                                                                                 |      |          |           |          |
| $t_{pd0}$ , $t_{pd1}$                                    | Propagation Delay Time to Logical "1" or "0"<br>$V_{CC} = 5.0\text{V}$<br>$V_{CC} = 10\text{V}$ |      | 70<br>40 | 115<br>80 | ns<br>ns |
| $C_{IN}$                                                 | Input Capacitance<br>(Note 2)                                                                   |      | 9        |           | pF       |
| $C_{PD}$                                                 | Power Dissipation Capacitance<br>(Note 3) Per Gate                                              |      | 30       |           | pF       |


**Note 1:** "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

**Note 2:** Capacitance is guaranteed by periodic testing.


**Note 3:**  $C_{PD}$  determines the no load ac power consumption of any CMOS device. For complete explanation see 54C/74C Family Characteristics application note — AN-90.

## Typical Performance Characteristics


Gate Transfer Characteristics




Guaranteed Noise Margin Over Temperature vs  $V_{CC}$




Power Dissipation vs Frequency  
MM54C00/MM74C00,  
MM54C02/MM74C02,  
MM54C04/MM74C04




Propagation Delay vs Ambient Temperature  
MM54C00/MM74C00,  
MM54C02/MM74C02,  
MM54C04/MM74C04




Propagation Delay vs Ambient Temperature  
MM54C00/MM74C00,  
MM54C02/MM74C02,  
MM54C04/MM74C04




Propagation Delay Time vs Load Capacitance  
MM54C00/MM74C00,  
MM54C02/MM74C02,  
MM54C04/MM74C04



## Typical Performance Characteristics (Cont'd)



## Switching Time Waveforms and AC Test Circuits



**NOTE:** DELAYS MEASURED WITH INPUT  $t_r, t_f \leq 20$  ns.