

# MPC5777C Microcontroller

Ultra-Reliable MCUs Built on Power Architecture® Technology

Product One-Sheet

Get Sample

Datasheet

Tools

**Multi-core Performance** – High performance and integration for powertrain control within a power envelope of previous-generation MCUs.

**Advanced Timers and ADCs** – eTPU timers and Sigma-Delta ADC converters allow for advanced filtering using on-chip knock hardware.

**Quality, Security and Redundancy** – AEC-Q100 qualification testing, on-chip security encryption protection using CSE and TDM for tamper proofing, and lockstep cores help support ASIL-D and SIL-1 functional safety (ISO26262/ IEC61508) requirements.

## Features

- ▶ AEC-Q100 Grade1, Ta 125°C
- ▶ Ethernet, CAN-FD
- ▶ Precision eTPU Timers and ADC
- ▶ Ultra-Reliable MCU


## Orderable Samples

Part Number	Temp Range	Package
SPC5777CCK3MME3	-40°C to 125°C	416-pin MAPBGA
SPC5777CCK3MMO3	-40°C to 125°C	516-pin MAPBGA

## MPC5777C Specifications

Flash	8 MB	Timer/PWM	96ch eTPU, 32ch eMIOS
RAM	512 KB	Other	128-ch DMA, ECC, 12ch SENT, Zipwire®, MSB, 2ch PSI-5
Cores	2x z7(1 in LS)	Analog	70-ch ADCs and 12-ch SD-ADCs
Speed	264 MHz/core	Ethernet	Ethernet (FEC)
Package	416 to 516 pins	SCI/SPI	5/5
Op Range	3.0 V - 5.5 V	CAN	2 x MCAN-FD and 4 x FlexCAN
Temp	-40°C to 125°C	Security	CSE, TDM, WDOG, CRC

## MPC5777C Block Diagram



## Success Stories

- ▶ Engine Management
- ▶ Hybrid and Electric Motors
- ▶ Transmissions

## Target Applications

- ▶ Safety Critical Applications
- ▶ Engine Control Units (ECU)
- ▶ Electric DC motor control
- ▶ Ethernet Connectivity
- ▶ Aerospace Engines

## Enablement Tools

- ▶ Evaluation Boards:
  - MPC5777C-416DS 416-pin adapter
  - MPC5777C-516DS 516-pin adapter
  - MPC57XXXMB motherboard
- ▶ S32 Design Studio (S32DS)
- ▶ NVM/Flash Drivers
- ▶ AUTOSAR MCAL drivers (SDK)
- ▶ GreenHills, Wind River (Diab)
- ▶ Lauterbach
- ▶ iSystem
- ▶ P&E Micro, ETAS and PLS



[www.nxp.com/MPC5777C](http://www.nxp.com/MPC5777C)

NXP, the NXP logo, Freescale, the Freescale logo, the Energy Efficient Solutions logo, the SafeAssure logo, and Layerscape are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. © 2016 NXP B.V.

Document Number: MPC5777CFS REV 0

