

Advance Information

MPC7410RXPDPNS/D
Rev. 1, 10/2002

MPC7410 Part Number
Specification for the
MPC7410RXnnnPD Series



Motorola Part Numbers Affected:

*XPC7410RX450PD
XPC7410RX500PD
XPC7410RX533PD*

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC7410 Hardware Specifications* (order #: MPC7410EC/D).

Specifications provided in this document supersede those in the *MPC7410 Hardware Specifications*, for the part numbers listed in Table A only. Specifications not addressed herein are unchanged. Because this document is frequently updated, refer to <http://www.motorola.com/semiconductors> or to your Motorola sales office for the latest version.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification. Part numbers addressed in this document are listed in Table A. For more detailed ordering information, see Table 17.

Features

Table A. Part Numbers Addressed by this Data Sheet

Motorola Part Number	Operating Conditions			Significant Differences from Hardware Specification
	CPU Frequency	Vdd	T _J (°C)	
XPC7410RX450PD	450 MHz	2.0V±50mV	0 to 65	Modified Voltage & Temperature Specification to achieve 450Mhz frequency
XPC7410RX500PD	500 MHz	2.0V±50mV	0 to 65	Modified Voltage & Temperature Specification to achieve 500Mhz frequency
XPC7410RX533PD	533 MHz	2.0V±50mV	0 to 65	Modified Voltage & Temperature Specification to achieve 533Mhz frequency

Note:

The X prefix in a Motorola PowerPC part number designates a “Pilot Production Prototype” as defined by Motorola SOP 3-13. These are from a limited production volume of prototypes manufactured, tested and Q.A. inspected on a qualified technology to simulate normal production. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.

1.2 Features

This section summarizes changes to the features of the MPC7410 described in the *MPC7410 Hardware Specifications*, which are none.

1.4.1 DC Electrical Characteristics

Table 3 provides the recommended operating conditions for the MPC7410 part numbers described herein.

Table 3. Recommended Operating Conditions

Characteristic	Symbol	Recommended Value	Unit	
Core supply voltage	Vdd	2.0V ± 50mV	V	
PLL supply voltage	AVdd	2.0V ±5 0mV	V	
L2 DLL supply voltage	L2AVdd	2.0V ± 50mV	V	
Processor bus supply voltage	BVSEL = 1 or BVSEL = HRESET	OVdd	2.5V ± 125mV	V
	BVSEL = GND	OVdd	1.8V ± 90mV	V
L2 bus supply voltage	L2VSEL = 1 or L2VSEL = HRESET	L2OVdd	2.5V ± 125mV	V
	L2VSEL = GND	L2OVdd	1.8V ± 90mV	V

Table 3. Recommended Operating Conditions (continued)

Characteristic		Symbol	Recommended Value	Unit
Input voltage	Processor bus	V_{in}	GND to OVdd	V
	L2 Bus	V_{in}	GND to L2OVdd	V
	JTAG Signals	V_{in}	GND to OVdd	V
Die-junction temperature		T_j	0-65	°C

Note:

These are the recommended and tested operating conditions. Proper device operation outside of these conditions is not guaranteed.

Table 6 provides the power consumption for the MPC7410 part at the frequencies described herein.

Table 6. Power Consumption for MPC7410

	Processor (CPU) Frequency	Processor (CPU) Frequency	Processor (CPU) Frequency	Unit	Notes
	450Mhz	500Mhz	533Mhz		
Full-On Mode					
Typical	5.9	6.5	6.9	W	1, 3
Maximum	13.2	14.7	15.6	W	1, 2
Doze Mode					
Maximum	4.5	5	5.3	W	1, 2
Nap Mode					
Maximum	2.13	2.25	2.33	W	1, 2
Sleep Mode					
Maximum	2.13	2.25	2.33	W	1, 2
Sleep Mode—PLL and DLL Disabled					
Typical	0.5	0.5	0.5	W	1, 3
Maximum	2.0	2.0	2.0	W	1, 2

Notes:

1. These values apply for all valid processor bus and L2 bus ratios. The values do not include I/O Supply Power (OVdd and L2OVdd) or PLL/DLL supply power (AVdd and L2AVdd). OVdd and L2OVdd power is system dependent, but is typically <10% of Vdd power. Worst case power consumption for AVdd = 15 mw and L2AVdd = 15 mW.
2. Maximum power is measured at 65 °C and Vdd = 2.0V while running an entirely cache-resident, contrived sequence of instructions which keep the execution units, including AltiVec, maximally busy.
3. Typical power is an average value measured at 65 °C and Vdd = 2.0V in a system while running typical benchmarks.

1.4.2.1 Clock AC Specifications

Table 7 provides the additional clock AC timing specifications described in this document. Refer to the *MPC7410 Hardware Specification* for the remaining frequencies.

Table 7. Clock AC Timing Specifications

At recommended operating conditions (See Table 3.)

Characteristic	Symbol	450 MHz		500 MHz		533 MHz		Unit	Notes
		Min	Max	Min	Max	Min	Max		
Processor frequency	f_{core}	300	450	300	500	300	533	MHz	
VCO frequency	f_{VCO}	600	900	600	1000	600	1066	MHz	
SYSCLK frequency	f_{SYSCLK}	33	133	33	133	33	133	MHz	1
SYSCLK cycle time	t_{SYSCLK}	7.5	30	7.5	30	7.5	30	ns	
SYSCLK rise and fall time	t_{KR}	—	1.0	—	1.0	—	1.0	ns	2
	t_{KF}	—	0.5	—	0.5	—	0.5	ns	3
SYSCLK duty cycle measured at $OV_{\text{dd}}/2$	$t_{\text{KHKL}}/t_{\text{SYSCLK}}$	40	60	40	60	40	60	%	4
SYSCLK jitter		—	± 150	—	± 150	—	± 150	ps	5
Internal PLL relock time		—	100	—	100	—	100	μs	6

Note:

See general hardware specification.

1.4.2.2 Processor Bus AC Specifications

Table 8 provides the processor bus AC timing specifications for the MPC7410 part described in this document.

Table 8. Processor Bus AC Timing Specifications

At $V_{dd}=AV_{dd}=2.0V\pm 50mV$; $0 \leq T_j \leq 65^\circ C$, $OV_{dd} = 2.5V\pm 0.125V$ and $OV_{dd} = 1.8V\pm 0.090V$, 60X bus at 133MHz

Parameter	Symbol	450, 500, 533 Mhz		Unit	Notes
		Min	Max		
Mode select input setup to \overline{HRESET}	t_{MVRH}	8	—	t_{sysclk}	2,3,4,5
\overline{HRESET} to mode select input hold	t_{MXRH}	0	—	ns	2,3,5
Setup Times:				ns	10
Address/Transfer Attribute	t_{AVKH}	1.4	—		6
Transfer Start (\overline{TS})	t_{TSVKH}	1.4	—		—
Data/Data Parity	t_{DVKH}	1.4	—		7
$\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$	t_{ARVKH}	1.4	—		—
All Other Inputs	t_{IVKH}	1.4	—		8
Input Hold Times:				ns	11
Address/Transfer Attribute	t_{AXKH}	0	—		6
Transfer Start (\overline{TS})	t_{TSXKH}	0	—		—
Data/Data Parity	t_{DXKH}	0	—		7
$\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$	t_{ARXKH}	0	—		—
All Other Inputs	t_{IXKH}	0	—		8
Valid Times:				ns	12
Address/Transfer Attribute	t_{KHAV}	—	3.0		6
\overline{TS} , \overline{ABB} , \overline{DBB}	t_{KHTSV}	—	3.0		—
Data	t_{KHdV}	—	3.5		7
Data Parity	t_{KHDPV}	—	3.5		7
$\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$	t_{KHARV}	—	2.3		—
All Other Outputs	t_{KHOV}	—	3.0		9
Output Hold Times:				ns	13
Address/Transfer Attribute	t_{KHAX}	0.75	—		6
\overline{TS} , \overline{ABB} , \overline{DBB}	t_{KHtSX}	0.75	—		—
Data/Data Parity	t_{KHdX}	0.6	—		7
$\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$	t_{KHARX}	0.75	—		—
All Other Outputs	t_{KHOX}	0.75	—		9
SYSCLK to Output Enable	t_{KHOE}	0.5	—	ns	14
SYSCLK to Output High Impedance (all except \overline{TS} , $\overline{ABB}/\overline{AMON}(0)$, $\overline{ARTRY}/\overline{SHD}$, $\overline{DBB}/\overline{DMON}(0)$)	t_{KHOZ}	—	3.5	ns	15

DC Electrical Characteristics

Table 8. Processor Bus AC Timing Specifications (continued)

At Vdd=AVdd=2.0V±50mV; 0 ≤ Tj ≤ 65°C, OVdd = 2.5V±0.125V and OVdd = 1.8V±0.090V, 60X bus at 133MHz

Parameter	Symbol	450, 500, 533 Mhz		Unit	Notes
		Min	Max		
SYSCLK to \overline{TS} , $\overline{ABB/AMON}(0)$, $\overline{DBB/DMON}(0)$ High Impedance after precharge	t _{KHABPZ}	—	1.0	t _{sysclk}	4,15,16,17
Maximum Delay to $\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$ Precharge	t _{KHARP}	—	1	t _{sysclk}	4,17
SYSCLK to $\overline{ARTRY}/\overline{SHD0}/\overline{SHD1}$ High Impedance After Precharge	t _{KHARPZ}	—	2	t _{sysclk}	4,17

Note:

See general hardware specification.

1.4.2.3 L2 Clock AC Specifications

Table 9 provides the L2CLK Output AC Timing Specifications for the MPC7410 part described in this document.

Table 9. L2CLK Output AC Timing Specifications

At recommended operating conditions (See Table 3.)

Parameter	Symbol	450 MHz		500 MHz		533 MHz		Unit	Notes
		Min	Max	Min	Max	Min	Max		
L2CLK frequency	f _{L2CLK}	150	225	150	250	150	266	MHz	1
L2CLK cycle time	t _{L2CLK}	4.4	6.67	4.0	6.67	3.76	6.67	ns	
L2CLK duty cycle	t _{CHCL} /t _{L2CLK}	50		50		50		%	2
Internal DLL-relock time		640	—	640	—	640	—	L2CLK	4
DLL capture window			±200		±200		±200	ns	5

Note:

See general hardware specification.

1.4.2.4 L2 Bus AC Specifications

Table 10 provides the L2 Bus Interface AC Timing Specifications for the frequencies described in this document.

Table 10. L2 Bus Interface AC Timing Specifications

At V_{dd}=AV_{dd}=L2AV_{dd}= 2.05V±50mV; 0 ≤ T_j ≤ 65°C, L2OV_{dd} = 2.5V±0.125V and L2OV_{dd} = 1.8V±0.090V

Parameter	Symbol	450 MHz		500 MHz		533 MHz		Unit	Notes
		Min	Max	Min	Max	Min	Max		
L2SYNC_IN rise and fall time	t _{L2CR} & t _{L2CF}	—	1.0	—	1.0	—	1.0	ns	1
Setup Times: Data and parity	t _{DVL2CH}	1.375	—	1.250	—	1.168	—	ns	2
Input Hold Times: Data and parity	t _{DXL2CH}	—	0.0	—	0.0	—	0.0	ns	2
Valid Times: All outputs when L2CR[14-15] = 00 All outputs when L2CR[14-15] = 01 All outputs when L2CR[14-15] = 10 All outputs when L2CR[14-15] = 11	t _{L2CHOV}	- - - -	2.375 TBD TBD TBD	- - - -	2.25 TBD TBD TBD	- - - -	2.17 TBD TBD TBD	ns	3,4
Output Hold Times All outputs when L2CR[14-15] = 00 All outputs when L2CR[14-15] = 01 All outputs when L2CR[14-15] = 10 All outputs when L2CR[14-15] = 11	t _{L2CHOX}	0.55 TBD TBD TBD	- - - -	0.5 TBD TBD TBD	- - - -	0.47 TBD TBD TBD	- - - -	ns	3
L2SYNC_IN to high impedance: All outputs when L2CR[14-15] = 00 All outputs when L2CR[14-15] = 01 All outputs when L2CR[14-15] = 10 All outputs when L2CR[14-15] = 11	t _{L2CHOZ}	- - - -	2.0 2.5 3.0 3.5	- - - -	2.0 2.5 3.0 3.5	- - - -	2.0 2.5 3.0 3.5	ns	

Note:

See general hardware specification.

1.9 Document Revision History

Table 16 provides a revision history for this Part Number Specification.

Table 16. Document Revision History

Document Revision	Substantive Changes
Rev 0	Initial Release
Rev 1	Minor formatting
	Section 1.10.1 - added Table 17 - Part-Marking Nomenclature

1.10 Ordering Information

1.10.1 Part Numbers Addressed by this Specification

Table 17 provides the ordering information for the MPC7410 part described in this document.

Table 17. Part-Marking Nomenclature

MPC 7410 RX xxx X X


Product Code	Part Identifier	Package	Processor Frequency ¹	Application Modifier	Revision Level
XPC ²	7410	RX = CBGA	450 500 533	P: 2.0 V ± 50 mV 0 to 65 °C	D: 1.3; PVR = 800C 1103

Notes:

1. Processor core frequencies supported by parts addressed by this specification only. Parts addressed by other specifications may support other maximum core frequencies.
2. The X prefix in a Motorola PowerPC part number designates a "Pilot Production Prototype" as defined by Motorola SOP 3-13. These are from a limited production volume of prototypes manufactured, tested and Q.A. inspected on a qualified technology to simulate normal production. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.

1.10.3 Part Marking

Parts are marked as the example shown in Figure 26.



Notes:

nnn is the speed grade of the part

MMMMMM is the 6-digit mask number

ATWLYYWWA is the traceability code

CCCCC is the country of assembly (this space is left blank if parts are assembled in the United States)

7410

BGA

Figure 26. Motorola Part Marking for BGA Device

Ordering Information

HOW TO REACH US:**USA/EUROPE/LOCATIONS NOT LISTED:**

Motorola Literature Distribution
P.O. Box 5405, Denver, Colorado 80217
1-303-675-2140 or 1-800-441-2447

JAPAN:

Motorola Japan Ltd.
SPS, Technical Information Center
3-20-1, Minami-Azabu Minato-ku
Tokyo 106-8573 Japan
81-3-3440-3569

ASIA/PACIFIC:

Motorola Semiconductors H.K. Ltd.
Silicon Harbour Centre, 2 Dai King Street
Tai Po Industrial Estate, Tai Po, N.T., Hong Kong
852-26668334

TECHNICAL INFORMATION CENTER:

1-800-521-6274

HOME PAGE:

<http://www.motorola.com/semiconductors>

DOCUMENT COMMENTS:

FAX (512) 933-2625
Attn: RISC Applications Engineering

Information in this document is provided solely to enable system and software implementers to use Motorola products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part.



Motorola and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. digital dna is a trademark of Motorola, Inc. All other product or service names are the property of their respective owners. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

© Motorola, Inc. 2002

MPC7410RXPDPNS/D