

GENERAL DESCRIPTION

The RM733/RC733 integrated circuit is a monolithic video amplifier with differential inputs and differential outputs. It offers three selectable voltage gains of 10, 100, or 400 and adjustable gain of 10 to 400 using a single resistor. No external frequency compensation is necessary for any gain option. The circuit and process designs are optimized to give a stable gain ($\pm 10\%$), wide bandwidth (DC to 120MHz), high input resistance (250k Ω), and low phase shift that is linear up to 10MHz (2° per MHz).

The RM733/RC733 is designed for use as a read head amplifier for magnetic tape, drum, or disc memories using phase of NRZ encoding. It will also function as a preamplifier for high speed film or plated wire memory systems; as a video or pulse amplifier, pulse height detector, peak detector.

Applications for the RM733/RC733 include bulk computer


memory systems, very high speed random access memory systems, communications systems, nuclear event instrumentation, frequency counters, and other systems where the specific design features of the RM733/RC733 are required.

The RM733 video amplifier will operate over the complete military temperature range from -55°C to +125°C while the commercial version, the RC733, operates from 0°C to +70°C.

DESIGN FEATURES

- Wide Bandwidth DC to 120MHz
- Low Linear Phase Shift 2°/MHz to 10MHz
- Selectable Voltage Gains 10, 100, or 400
- Excellent Pulse Characteristics
- High Input Resistance 250k Ω

SCHEMATIC DIAGRAM



CONNECTION INFORMATION

DB and DC Dual In Line Packages (Top View)	TF Metal Can Package (Top View) G2A GAIN SELECT	CQ Flat Pack Package
Order Part Nos.: RM733DC, RC733DC, RC733DB	Order Part Nos.: RM733T RC733T	Order Part Nos.: RM733CQ

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	$\pm 8.0V$	Operating Temperature Range	$-55^{\circ}C$ to $+125^{\circ}C$
Differential Input Voltage	$\pm 5.0V$	RM733	$0^{\circ}C$ to $+70^{\circ}C$
Common Mode Input Voltage	$\pm 6.0V$	RC733	$-65^{\circ}C$ to $+150^{\circ}C$
Input Current	10mA	Storage Temperature Range	$-65^{\circ}C$ to $+150^{\circ}C$
Internal Power Dissipation Metal Can (Note 1)	500mW	Lead Temperature (Soldering, 60s)	300°C
Flat Pack	570mW		

ELECTRICAL CHARACTERISTICS (Note 2)

PARAMETER (Note 3)	CONDITIONS	RM733			RC733			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
Differential Voltage Gain	Gain 1	300	400	500	250	400	600	
	Gain 2	90	100	110	80	100	120	
	Gain 3	9.0	10	11	8.0	10	12	
Bandwidth	Gain 1		40			40		MHz
	Gain 2	$R_S = 50\Omega$	90			90		
	Gain 3		120			120		
Risetime	Gain 1	$R_S = 50\Omega, V_{OUT} = 1V_{PP}$	10.5			10.5		ns
	Gain 2		4.5	10		4.5	12	
	Gain 3		2.5			2.5		
Propagation Delay	Gain 1	$R_S = 50\Omega, V_{OUT} = 1V_{PP}$	7.5			7.5		ns
	Gain 2		6.0	10		6.0	10	
	Gain 3		3.6			3.6		
Input Resistance	Gain 1		4.0			4.0		$k\Omega$
	Gain 2		20	30		10	30	
	Gain 3			250			250	
Input Capacitance	Gain 2		2.0			2.0		pF
Input Offset Current			0.4	3.0		0.4	5.0	μA
Input Bias Current			9.0	20		9.0	30	μA
Input Noise Voltage	$R_S = 50\Omega, BW = 1kHz$ to $10MHz$		12			12		μV_{rms}
Input Voltage Range		± 1.0			± 1.0			V
Common Mode Rejection Ratio	Gain 2	$V_{CM} = \pm 1V, R \leq 100kHz$	60	86		60	86	dB
		$V_{CM} = \pm 1V, f = 5MHz$		60			60	
Supply Voltage Rejection Ratio	Gain 2	$\Delta V_S = \pm 0.5V$	50	70		50	70	dB
Output Offset Voltage	Gain 1		0.6	1.5		0.6	1.5	V
	Gain 2 Gain 3		0.35	1.0		0.35	1.5	
Output Common Mode Voltage			2.4	2.9	3.4	2.4	2.9	3.4
Output Voltage Swing			3.0	4.0		3.0	4.0	V_{PP}
Output Sink Current			2.5	3.6		2.5	3.6	mA
Output Resistance				20			20	Ω
Power Supply Current				18	24		18	24
								mA

NOTES:

- For RM733 the rating applies for case temperature to $+125^{\circ}C$; derate RM733T linearly at $6.5 mW/^{\circ}C$ for ambient temperature above $75^{\circ}C$. For RC733T, the rating applies for ambient temperatures to $70^{\circ}C$. For RM733CQ, derate linearly at $7.2 mW/^{\circ}C$ for ambient temperature above $75^{\circ}C$.
- $V_S = \pm 6.0V; T_A = 25^{\circ}C$ unless otherwise noted.
- Gain 1: G1A and G1B connected together; Gain 2: G2A and G2B connected together; Gain 3: Gain select pins open.



ELECTRICAL CHARACTERISTICS(The following specifications apply for $-55^{\circ}\text{C} \leq T_A \leq 125^{\circ}\text{C}$ for the RM733 and $0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$ for the RC733, $V_S = \pm 6.0\text{V}$)

PARAMETER	CONDITIONS	LM733			LM733C			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
Differential Voltage Gain Gain 1		200		600	250		600	
Gain 2		80		120	80		120	
Gain 3		8.0		12.0	8.0		12.0	
Input Resistance Gain 2		8			8			$\text{k}\Omega$
Input Offset Current				5			6	μA
Input Bias Current				40			40	μA
Input Voltage Range		± 1			± 1			V
Common-Mode Rejection Ratio Gain 2		50			50			dB
Supply Voltage Rejection Ratio Gain 2		50			50			db
Output Offset Voltage Gain 1				1.5			1.5	V
Gain 2 and 3				1.2			1.5	V
Output Voltage Swing		2.5			2.8			V p-p
Output Sink Current		2.2			2.5			mA
Power Supply Current				27			27	mA