


POWER SCHOTTKY RECTIFIER

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- EXTREMELY FAST SWITCHING
- LOW FORWARD VOLTAGE DROP
- HIGH AVALANCHE CAPABILITY
- LOW THERMAL RESISTANCE
- INSULATED PACKAGE :
 - Insulating voltage = 2000V DC
 - Capacitance = 12pF

DESCRIPTION

Single chip schottky rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged in TO220AC and ISOWATT220AC, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit
$I_{F(RMS)}$	RMS Forward Current			30	A
$I_{F(AV)}$	Average Forward Current $\delta = 0.5$	TO220AC	$T_c = 135^\circ C$	15	A
		ISOWATT220AC	$T_c = 105^\circ C$		
I_{FSM}	Surge Non Repetitive Forward Current		$T_p = 10 \text{ ms}$ Sinusoidal	220	A
I_{RRM}	Peak Repetitive Reverse Current		$T_p = 2 \mu s$ $F = 1 \text{ KHz}$	1	A
T_{stg} T_j	Storage and Junction Temperature Range			- 65 to + 150 - 65 to + 150	°C
dV/dt	Critical Rate of Rise of Reverse Voltage			1000	V/ μ s

Symbol	Parameter	STPS		Unit
		1535D 1535F	1545D 1545F	
$V_{R(RM)}$	Repetitive Peak Reverse Voltage	35	45	V

THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
$R_{TH(j-c)}$	Junction-case	TO220AC	1.6
		ISOWATT220AC	4.0

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

Symbol	Tests Conditions		Min.	Typ.	Max.	Unit
I_R *	$T_J = 25^\circ C$	$V_R = V_{RRM}$			200	μA
	$T_J = 125^\circ C$				40	mA
V_F **	$T_J = 125^\circ C$	$I_F = 30 A$			0.72	V
	$T_J = 125^\circ C$	$I_F = 15 A$			0.57	
	$T_J = 25^\circ C$	$I_F = 30 A$			0.84	

Pulse test : * tp = 5 ms, duty cycle < 2 %

** tp = 380 μs , duty cycle < 2%

To evaluate the conduction losses use the following equation :

$$P = 0.42 \times I_{F(AV)} + 0.01 I_{F}^2(RMS)$$

Fig. 1 : Average forward power dissipation versus average forward current.




Fig. 2 : Average current versus ambient temperature.
(duty cycle : 0.5) (TO220AC)




Fig. 4 : Non repetitive surge peak forward current versus overload duration.
(Maximum values) (TO220AC)




Fig. 6 : Relative variation of thermal transient impedance junction to case versus pulse duration.
(TO220AC)




Fig. 3 : Average current versus ambient temperature.
(duty cycle : 0.5) (ISOWATT220AC)




Fig. 5 : Non repetitive surge peak forward current versus overload duration.
(Maximum values) (ISOWATT220AC)




Fig. 7 : Relative variation of thermal transient impedance junction to case versus pulse duration.
(ISOWATT220AC)




Fig. 8 : Reverse leakage current versus reverse voltage applied. (Typical values)




Fig. 9 : Junction capacitance versus reverse voltage applied. (Typical values)




Fig. 10 : Forward voltage drop versus forward current. (Maximum values)

