



6AR5

POWER PENTODE

MINIATURE TYPE

6ARS

GENERAL DATA**Electrical:**


Heater, for Unipotential Cathode:

Voltage.	6.3	ac or dc volts
Current.	0.4	amp

Mechanical:

Mounting Position.	Any
Maximum Overall Length	2-5/8"
Maximum Seated Length.	2-3/8"
Length, Base Seat to Bulb Top (excluding tip).	2" ± 3/32"
Maximum Diameter	3/4"
Bulb	T-5-1/2
Base	Small-Button Miniature 7-Pin
Basing Designation for BOTTOM VIEW	6CC

Pin 1 - Grid No.1
 Pin 2 - Cathode,
 Grid No.3
 Pin 3 - Heater
 Pin 4 - Heater



Pin 5 - Plate
 Pin 6 - Grid No.2
 Pin 7 - No
 Connection

AF POWER AMPLIFIER - Class A₁**Maximum Ratings, Design-Center Values:**

PLATE VOLTAGE.	250 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	250 max.	volts
PLATE DISSIPATION.	8.5 max.	watts
GRID-No.2 DISSIPATION.	2.5 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	90 max.	volts
Heater positive with respect to cathode.	90 max.	volts

Typical Operation and Characteristics:

Plate Voltage.	250	250	volts
Grid-No.2 Voltage.	250	250	volts
Grid-No.1 (Control-Grid) Voltage	-16.5	-18	volts
Peak AF Grid-No.1 Voltage.	16.5	18	volts
Zero-Signal Plate Current.	34	32	ma
Max.-Signal Plate Current.	35	33	ma
Zero-Signal Grid-No.2 Current.	5.7	5.5	ma
Max.-Signal Grid-No.2 Current.	10	10	ma
Plate Resistance (Approx.)	65000	68000	ohms
Transconductance	2400	2300	μ hos
Load Resistance.	7000	7600	ohms
Total Harmonic Distortion.	7	11	%
Max.-Sig. Power Output	3.2	3.4	watts

(continued on next page)

6AR5



6AR5

POWER PENTODE

Maximum Circuit Values (for maximum rated conditions):

Grid-No.1-Circuit Resistance:

For fixed bias. 0.1 max. megohm

For cathode bias. 0.5 max. megohm

*Curves for the 6AR5 are the same as those
shown for type 6K6-GT.*

MAY 20, 1949

TUBE DEPARTMENT

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA