



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|--------|--------|
| | MIN | MAX | MIN | MAX |
| A | 4.06 | 4.57 | 0.160 | 0.180 |
| B | 3.30 | 3.81 | 0.130 | 0.150 |
| C | 1.90 | 2.41 | 0.075 | 0.095 |
| D | 1.96 | 2.11 | 0.077 | 0.083 |
| H | 0.051 | 0.152 | 0.0020 | 0.0060 |
| J | 0.15 | 0.30 | 0.006 | 0.012 |
| K | 0.76 | 1.27 | 0.030 | 0.050 |
| P | 0.51 | REF | 0.020 | REF |
| S | 5.21 | 5.59 | 0.205 | 0.220 |

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. D DIMENSION SHALL BE MEASURED WITHIN DIMENSION P.

CASE NO. 403C-01
 STATUS ON Semiconductor Standard
 NEW STD
 USED ON

ON Semiconductor

| | |
|----------|-------------|
| DOC. NO. | 98ARB18918C |
| PAGE NO. | 2 of 2 |

| ISSUE | REVISION | COORD/ DATE |
|-------|--------------------------------------------------------------------------------------------------------------------------------|-------------------|
| O | INITIATED NEW MECHANICAL OUTLINE # 403C. REQ BY D. WAHL. | FB 15 MAR 1999 |
| A | Revision to change legal ownership of document from Motorola to ON Semiconductor. Written by C. Payne; approved by Damien Balk | ME 02 Jan 2000 |