

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

## TYPES 2N4998, 2N5000, 2N5148, 2N5150 N-P-N SILICON POWER TRANSISTORS

### HIGH-FREQUENCY POWER TRANSISTORS WITH COMPUTER-DESIGNED ISOTHERMAL GEOMETRY

- For Complementary Use With 2N4999, 2N5001, 2N5147, and 2N5149
- 6 mJ Reverse Energy Rating with  $I_C = 5 \text{ A}$  and 4 V Reverse Bias

\*mechanical data

2N4998, 2N5000    ALL TERMINALS ARE INSULATED FROM THE CASE	2N5148, 2N5150    THE COLLECTOR IS IN ELECTRICAL CONTACT WITH THE CASE
<p>ALL JEDEC TO-59 DIMENSIONS AND NOTES ARE APPLICABLE</p> <p>NOTES: A. Within this dimension, case diameter may vary. B. Position of terminals with respect to hexagon is not controlled. C. The case temperature may be measured anywhere on the seating plane within 0.125 inch of the stud. D. All dimensions are in inches unless otherwise specified.</p>	<p>ALL JEDEC TO-39 DIMENSIONS AND NOTES ARE APPLICABLE</p> <p>ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.</p>

absolute maximum ratings at 25°C case temperature (unless otherwise noted)

	2N4998	2N5148
Collector-Base Voltage	100 V*	80 V*
Collector-Emitter Voltage (See Note 1)	80 V*	6 V*
Emitter-Base Voltage		
Continuous Collector Current	2 A*	2 A*
Peak Collector Current (See Note 2)	5 A*	5 A*
Continuous Base Current	1 A*	1 A*
Safe Operating Areas		
Continuous Device Dissipation at 50°C Case Temperature (See Note 3)	30 W*	6 W*
Continuous Device Dissipation at 100°C Case Temperature (See Note 3)	20 W	4 W
Continuous Device Dissipation at (or below) 25°C Free-Air Temperature (See Note 4)	2 W	1 W*
Unclamped Inductive Load Energy (See Note 5)	6 mJ	
Operating Collector Junction Temperature Range	-65°C to 200°C*	-65°C to 200°C*
Storage Temperature Range	-65°C to 200°C*	-65°C to 200°C*
Lead or Terminal Temperature 1/8 inch from Case for 60 Seconds	300°C*	

NOTES: 1. This value applies when the base-emitter diode is open-circuited.  
2. This value applies for  $t_{on} \leq 8.3 \text{ ms}$ , duty cycle  $\leq 1\%$ .  
3. For operation above (or below) 50°C case temperature, refer to Dissipation Derating Curves Figures 9 and 10.  
4. Derate linearly to 200°C free-air temperature at the rate of 11.4 mW°C for 2N4998 and 2N5000, 5.7 mW°C for 2N5148 and 2N5150.  
5. This rating is based on the capability of the transistors to operate safely in the unclamped inductive load circuit of Section 3.2 of the forthcoming JEDEC publication Suggested Standards on Power Transistors†.  $L = 0.48 \text{ mH}$ ,  $R_{BB1} = 20 \Omega$ ,  $R_{BB2} = 100 \Omega$ ,  $V_{BB1} = 10 \text{ V}$ ,  $V_{BB2} = 4 \text{ V}$ ,  $R_L = 0.1 \Omega$ ,  $V_{CC} = 10 \text{ V}$ ,  $I_{CM} = 5 \text{ A}$ , Energy  $\approx I_C^2 L/2$ .

\* JEDEC registered trade. This data sheet contains all applicable registered data in effect at the time of publication.

† This circuit appears on page B-1 of this data book.

NJ Semi-Conductors reserves the right to change test conditions, parameters limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

**TYPES 2N4998, 2N5000, 2N5148, 2N5150**  
**N-P-N SILICON POWER TRANSISTORS**

\*electrical characteristics at 25°C case temperature (unless otherwise noted)

PARAMETER	TEST CONDITIONS	2N4998		2N5000		UNIT
		2N5148	2N5150	MIN	MAX	
V(BR)CEO Collector-Emitter Breakdown Voltage	I <sub>C</sub> = 100 mA, I <sub>B</sub> = 0, See Note 6	80	80	80	80	V
I <sub>CEO</sub> Collector Cutoff Current	V <sub>CE</sub> = 40 V, I <sub>B</sub> = 0	50	50	50	50	μA
I <sub>CES</sub> Collector Cutoff Current	V <sub>CE</sub> = 60 V, V <sub>BE</sub> = 0	1	1	1	1	mA
I <sub>CEV</sub> Collector Cutoff Current	V <sub>CE</sub> = 100 V, V <sub>BE</sub> = 0	1	1	1	1	mA
I <sub>CEV</sub> Collector Cutoff Current	V <sub>CE</sub> = 60 V, V <sub>BE</sub> = -2 V, T <sub>C</sub> = 150°C	500	500	500	500	mA
I <sub>EBO</sub> Emitter Cutoff Current	V <sub>EB</sub> = 5 V, I <sub>C</sub> = 0	1	1	1	1	μA
I <sub>EBO</sub> Emitter Cutoff Current	V <sub>EB</sub> = 6 V, I <sub>C</sub> = 0	1	1	1	1	mA
h <sub>FE</sub> Static Forward Current Transfer Ratio	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 50 mA	20	50			
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 1 A	30	90	70	200	
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 2 A	15	30			
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 3 A	5	15			
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 1 A, T <sub>C</sub> = -55°C	15	35			
V <sub>BE</sub> Base-Emitter Voltage	I <sub>B</sub> = 100 mA, I <sub>C</sub> = 1 A	1.2	1.2			
	I <sub>B</sub> = 200 mA, I <sub>C</sub> = 2 A	1.5	1.5			
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 2 A	1.5	1.5			
	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 3 A	3	3			
V <sub>CE(sat)</sub> Collector-Emitter Saturation Voltage	I <sub>B</sub> = 100 mA, I <sub>C</sub> = 1 A	0.46	0.46			
	I <sub>B</sub> = 200 mA, I <sub>C</sub> = 2 A	0.85	0.85			
	I <sub>B</sub> = 600 mA, I <sub>C</sub> = 3 A	5	5			
h <sub>fe</sub> Small-Signal Common-Emitter Forward Current Transfer Ratio	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 0.1 A, f = 1 kHz	20	50			
h <sub>te</sub> Small-Signal Common-Emitter Forward Current Transfer Ratio	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 0.2 A, f = 20 MHz	2.5	3			
C <sub>obo</sub> Common-Base Open-Circuit Output Capacitance	V <sub>CB</sub> = 10 V, I <sub>E</sub> = 0, f = 1 MHz	70	70	70	70	pF

NOTES: 6. These parameters must be measured using pulse techniques, t<sub>W</sub> = 300 μs, duty cycle ≤ 1%.

7. These parameters are measured with voltage-sensing contacts separate from the current-carrying contacts and located within 0.125 inch from the device body.

\* JEDEC registered data

**thermal characteristics**

PARAMETER	TEST CONDITIONS	2N4998		2N5148		UNIT
		2N5000	2N5150	MAX	MAX	
R <sub>jjc</sub> Junction-to-Case Thermal Resistance		5	25			°C/W
R <sub>ffa</sub> Junction-to-Free-Air Thermal Resistance		87.5	175			

**switching characteristics at 25°C case temperature**

PARAMETER	TEST CONDITIONS†	ALL TYPES		UNIT
		Typ	Typ	
t <sub>on</sub> Turn-On Time	I <sub>C</sub> = 2 A, I <sub>B(1)</sub> = 200 mA, I <sub>B(2)</sub> = -200 mA, See Figure 1	0.1	0.1	μs
t <sub>off</sub> Turn-Off Time	V <sub>BE(off)</sub> = -3.7 V, R <sub>L</sub> = 15 Ω,	1.1	1.1	

† Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.