

Medium Power Transistor (25V, 1.2A)

2SD2537 / 2SD2171S

●Features

- 1) High DC current gain.
- 2) High emitter-base voltage. ($V_{CE0}=12V$ Min.)
- 3) Low $V_{CE(sat)}$. (Max. 0.3V at $I_C/I_E=500/10mA$)

●Packaging specifications and hFE

Type	2SD2537	2SD2171S
Package	MPT3	SPT
hFE	VW	V
Marking	DV*	—
Code	T100	TP
Basic ordering unit (pieces)	1000	5000

* Denotes hFE

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	30	—	—	V	$I_C=10\mu A$
Collector-emitter breakdown voltage	BV_{CEO}	25	—	—	V	$I_C=1mA$
Emitter-base breakdown voltage	BV_{EBO}	12	—	—	V	$I_E=10\mu A$
Collector cutoff current	I_{CBO}	—	—	0.3	μA	$V_{CB}=30V$
Emitter cutoff current	I_{EBO}	—	—	0.3	μA	$V_{EB}=12V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	—	0.3	V	$I_C/I_E=500mA/10mA$ *
DC current transfer ratio	hFE	820	—	2700	—	$V_{CE}/I_C=5V/0.5A$
		820	—	1800	—	
Transition frequency	f _T	—	200	—	MHz	$V_{CE}=10V, I_E=-50mA, f=100MHz$ *
Output capacitance	C _{ob}	—	20	—	pF	$V_{CB}=10V, I_E=0A, f=1MHz$

* Measured using pulse current.

(94L-1061-D212)

●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CBO}	30	V
Collector-emitter voltage	V_{CEO}	25	V
Emitter-base voltage	V_{EBO}	12	V
Collector current	I_C	1.2	A (DC)
		2	A (Pulse) *1
Collector power dissipation	P_C	2	W *2
		0.3	
Junction temperature	T _J	150	°C
Storage temperature	T _{stg}	-55~150	°C

*1 Single pulse P_w=100ms *2 On 40 x 40 x 0.7 mm ceramic board.

General Purpose Transistor (50V, 0.15A)

2SD2351 / 2SD2226K / 2SD2227S

●Features

- 1) High DC current gain.
- 2) High emitter-base voltage. ($V_{CBO}=12V$ Min.)
- 3) Low $V_{CE(sat)}$. (Typ. 0.3V at $I_C/I_E=50/5mA$)

●Packaging specifications and hFE

Type	2SD2351	2SD2226K	2SD2227S
Package	UMT3	SMT3	SPT
hFE	VW	VW	W
Marking	BJ*	BJ*	—
Code	T106	T146	TP
Basic ordering unit (pieces)	3000	3000	5000

* Denotes hFE

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	60	—	—	V	$I_C=10\mu A$
Collector-emitter breakdown voltage	BV_{CEO}	50	—	—	V	$I_C=1mA$
Emitter-base breakdown voltage	BV_{EBO}	12	—	—	V	$I_E=10\mu A$
Collector cutoff current	I_{CBO}	—	—	0.3	μA	$V_{CB}=50V$
Emitter cutoff current	I_{EBO}	—	—	0.3	μA	$V_{EB}=12V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	—	0.3	V	$I_C/I_E=50mA/5mA$ *
DC current transfer ratio	hFE	560	—	2700	—	$V_{CE}/I_C=5V/1mA$ *
		1200	—	2700	—	$V_{CE}/I_C=5V/1mA$ *
Transition frequency	f _T	—	250	—	MHz	$V_{CE}=5V, I_E=-10mA, f=100MHz$ *
Output capacitance	C _{ob}	—	3.5	—	pF	$V_{CB}=5V, I_E=0A, f=1MHz$

* Measured using pulse current.

(94S-374-D215)

●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CBO}	60	V
Collector-emitter voltage	V_{CEO}	50	V
Emitter-base voltage	V_{EBO}	12	V
Collector current	I_C	0.15	A (DC)
		0.2	A (Pulse) *
Collector power dissipation	P_C	0.2	W
		0.3	
Junction temperature	T _J	150	°C
Storage temperature	T _{stg}	-55~150	°C

* Single pulse P_w=100ms

Notes

- The contents described in this catalogue are correct as of March 1997.
- No unauthorized transmission or reproduction of this book, either in whole or in part, is permitted.
- The contents of this book are subject to change without notice. Always verify before use that the contents are the latest specifications. If, by any chance, a defect should arise in the equipment as a result of use without verification of the specifications, ROHM CO., LTD., can bear no responsibility whatsoever.
- Application circuit diagrams and circuit constants contained in this data book are shown as examples of standard use and operation. When designing for mass production, please pay careful attention to peripheral conditions.
- Any and all data, including, but not limited to application circuit diagrams, information, and various data, described in this catalogue are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO., LTD., disclaims any warranty that any use of such device shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes absolutely no liability in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices; other than for the buyer's right to use such devices itself, resell or otherwise dispose of the same; no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by ROHM CO., LTD., is granted to any such buyer.

The products listed in this catalogue are designed to be used with ordinary electronic equipment or devices (such as audio-visual equipment, office-automation equipment, communications devices, electrical appliances, and electronic toys). Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers, or other safety devices) please be sure to consult with our sales representatives in advance.

- Notes when exporting
 - It is essential to obtain export permission when exporting any of the above products when it falls under the category of strategic material (or labor) as determined by foreign exchange or foreign trade control laws.
 - Please be sure to consult with our sales representatives to ascertain whether any product is classified as a strategic material.