

---

# **2SK2796 (L), 2SK2796 (S)**

Silicon N Channel MOS FET  
High Speed Power Switching

**HITACHI**


ADE-208-534 A  
2nd. Edition

---

## **Features**

- Low on-resistance  
 $R_{DS(on)} = 0.12\Omega$  typ.
- 4V gate drive devices.
- High speed switching

## **Outline**



---

**2SK2796 (L), 2SK2796 (S)**

---

**Absolute Maximum Ratings (Ta = 25°C)**

Item	Symbol	Ratings	Unit
Drain to source voltage	V <sub>DSS</sub>	60	V
Gate to source voltage	V <sub>GSS</sub>	±20	V
Drain current	I <sub>D</sub>	5	A
Drain peak current	I <sub>D(pulse)</sub> <sup>*1</sup>	20	A
Body to drain diode reverse drain current	I <sub>DR</sub>	5	A
Avalanche current	I <sub>AP</sub> <sup>*3</sup>	5	A
Avalanche energy	E <sub>AR</sub> <sup>*3</sup>	2.14	mJ
Channel dissipation	P <sub>ch</sub> <sup>*2</sup>	20	W
Channel temperature	T <sub>ch</sub>	150	°C
Storage temperature	T <sub>stg</sub>	−55 to +150	°C

Notes: 1. PW ≤ 10μs, duty cycle ≤ 1 %

2. Value at T<sub>c</sub> = 25°C

3. Value at T<sub>ch</sub> = 25°C, R<sub>g</sub> = 50 Ω

**HITACHI**

## **2SK2796 (L), 2SK2796 (S)**


### **Electrical Characteristics (Ta = 25°C)**

<b>Item</b>	<b>Symbol</b>	<b>Min</b>	<b>Typ</b>	<b>Max</b>	<b>Unit</b>	<b>Test Conditions</b>
Drain to source breakdown voltage	V <sub>(BR)DSS</sub>	60	—	—	V	I <sub>D</sub> = 10mA, V <sub>GS</sub> = 0
Gate to source breakdown voltage	V <sub>(BR)GSS</sub>	±20	—	—	V	I <sub>G</sub> = ±100μA, V <sub>DS</sub> = 0
Zero gate voltage drain current	I <sub>DSS</sub>	—	—	10	μA	V <sub>DS</sub> = 60 V, V <sub>GS</sub> = 0
Gate to source leak current	I <sub>GSS</sub>	—	—	±10	μA	V <sub>GS</sub> = ±16V, V <sub>DS</sub> = 0
Gate to source cutoff voltage	V <sub>GS(off)</sub>	1.0	—	2.0	V	I <sub>D</sub> = 1mA, V <sub>DS</sub> = 10V
Static drain to source on state resistance	R <sub>DS(on)</sub>	—	0.12	0.16	Ω	I <sub>D</sub> = 3 A, V <sub>GS</sub> = 10V <sup>*1</sup>
Forward transfer admittance	y <sub>fs</sub>	2.5	4.0	—	S	I <sub>D</sub> = 3A, V <sub>DS</sub> = 10V <sup>*1</sup>
Input capacitance	C <sub>iss</sub>	—	180	—	pF	V <sub>DS</sub> = 10V
Output capacitance	C <sub>oss</sub>	—	90	—	pF	V <sub>GS</sub> = 0
Reverse transfer capacitance	C <sub>rss</sub>	—	30	—	pF	f = 1MHz
Turn-on delay time	t <sub>d(on)</sub>	—	9	—	ns	V <sub>GS</sub> = 10V, I <sub>D</sub> = 3A
Rise time	t <sub>r</sub>	—	25	—	ns	R <sub>L</sub> = 12Ω
Turn-off delay time	t <sub>d(off)</sub>	—	35	—	ns	
Fall time	t <sub>f</sub>	—	55	—	ns	
Body to drain diode forward voltage	V <sub>DF</sub>	—	1.0	—	V	I <sub>D</sub> = 5A, V <sub>GS</sub> = 0
Body to drain diode reverse recovery time	t <sub>rr</sub>	—	40	—	ns	I <sub>F</sub> = 5A, V <sub>GS</sub> = 0 dI/F / dt = 50A/μs

Note: 1. Pulse test


## **2SK2796 (L), 2SK2796 (S)**

### **Main Characteristics**




**HITACHI**

## 2SK2796 (L), 2SK2796 (S)




**HITACHI**

## 2SK2796 (L), 2SK2796 (S)




**HITACHI**

## 2SK2796 (L), 2SK2796 (S)



**HITACHI**

## 2SK2796 (L), 2SK2796 (S)



**HITACHI**


---

## **2SK2796 (L), 2SK2796 (S)**

---

### **Package Dimensions**

**Unit: mm**



---

## **2SK2796 (L), 2SK2796 (S)**

---

When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. MEDICAL APPLICATIONS: Hitachi's products are not authorized for use in MEDICAL APPLICATIONS without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in MEDICAL APPLICATIONS.

---

# **HITACHI**

### **Hitachi, Ltd.**

Semiconductor & IC Div.

Nippon Bldg., 2-6-2, Ohtemachi, Chiyoda-ku, Tokyo 100, Japan

Tel: Tokyo (03) 3270-2144

Fax: (03) 3270-5109

For further information write to:

Hitachi America, Ltd.  
Semiconductor & IC Div.  
2000 Sierra Point Parkway  
Brisbane, CA. 94005-4835  
U.S.A.  
Tel: 415-583-8300  
Fax: 415-583-4207

Hitachi Europe GmbH  
Electronic Components Group  
Continental Europe  
Darmstader Straße 3  
D-85622 Fildkirchen  
München  
Tel: 089-9 91 80-0  
Fax: 089-9 29 30 00

Hitachi Europe Ltd.  
Electronic Components Div.  
Northern Europe Headquarters  
Whitebrook Park  
Lower Cookham Road  
Maidenhead  
Berkshire SL6 8YA  
United Kingdom  
Tel: 0628-595000  
Fax: 0628-778322

Hitachi Asia Pte. Ltd.  
16 Collyer Quay #20-00  
Hitachi Tower  
Singapore 0104  
Tel: 535-2100  
Fax: 535-1500

Hitachi Asia (Hong Kong) Ltd.  
Unit 706, North Tower,  
World Finance Centre  
Harbour City, Canton Road  
Tsui She Tsui, Kowloon  
Hong Kong  
Tel: 27359218  
Fax: 27308074

Copyright © Hitachi, Ltd., 1997. All rights reserved. Printed in Japan.

# **HITACHI**