

# DATA SHEET

## **BF861A; BF861B; BF861C** N-channel junction FETs

Product specification  
File under Discrete Semiconductors, SC07

1995 Apr 14

**Philips Semiconductors**



**PHILIPS**

# N-channel junction FETs

# BF861A; BF861B; BF861C

### FEATURES

- High transfer admittance
- Low input capacitance
- Low feedback capacitance
- Low noise.

### APPLICATIONS

- Preamplifiers for AM tuners in car radios.

### DESCRIPTION

N-channel symmetrical junction field effect transistors in a SOT23 package.

### PINNING - SOT23

PIN	SYMBOL	DESCRIPTION
1	g	gate
2	s	source
3	d	drain




Fig.1 Simplified outline and symbol.

### CAUTION

The device is supplied in an antistatic package. The gate-source input must be protected against static discharge during transport or handling.

### QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{DS}$	drain-source voltage (DC)		–	25	V
$I_{DSS}$	drain current BF861A BF861B BF861C	$V_{GS} = 0; V_{DS} = 8\text{ V}$	2 6 12	6.5 15 25	mA mA mA
$P_{tot}$	total power dissipation	up to $T_{amb} = 25\text{ °C}$	–	250	mW
$ y_{fs} $	forward transfer admittance BF861A BF861B BF861C	$V_{GS} = 0; V_{DS} = 8\text{ V}$	12 16 20	20 25 30	mS mS mS
$C_{iss}$	input capacitance	$f = 1\text{ MHz}$	–	10	pF
$C_{rss}$	reverse transfer capacitance	$f = 1\text{ MHz}$	–	2.7	pF

N-channel junction FETs

BF861A; BF861B; BF861C


**LIMITING VALUES**

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{DS}$	drain-source voltage (DC)		–	25	V
$V_{GSO}$	gate-source voltage	open drain	–	25	V
$V_{DGO}$	drain-gate voltage (DC)	open source	–	25	V
$I_G$	forward gate current (DC)		–	10	mA
$P_{tot}$	total power dissipation	up to $T_{amb} = 25\text{ °C}$ ; note 1	–	250	mW
$T_{stg}$	storage temperature		–65	+150	°C
$T_j$	operating junction temperature		–	150	°C

**Note**

1. Device mounted on an FR4 printed-circuit board.



## N-channel junction FETs

## BF861A; BF861B; BF861C

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
$R_{th\ j-a}$	thermal resistance from junction to ambient; note 1	500	K/W

## Note

1. Device mounted on an FR4 printed-circuit board.





## CHARACTERISTICS

$T_j = 25\text{ °C}$ ;  $V_{DS} = 8\text{ V}$ ;  $V_{GS} = 0$ ; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(BR)GSS}$	gate-source breakdown voltage	$I_G = -1\ \mu\text{A}$	-25	-	-	V
$V_{GSoff}$	gate-source cut-off voltage	$I_D = 1\ \mu\text{A}$				
	BF861A		-0.2	-	-1	V
	BF861B		-0.5	-	-1.5	V
	BF861C		-0.8	-	-2	V
$V_{GSS}$	gate-source forward voltage	$V_{DS} = 0$ ; $I_G = 1\ \text{mA}$	-	-	1	V
$I_{DSS}$	drain current					
	BF861A		2	-	6.5	mA
	BF861B		6	-	15	mA
	BF861C		12	-	25	mA
$I_{GSS}$	gate cut-off current	$V_{GS} = -20\ \text{V}$ ; $V_{DS} = 0$	-	-	-1	nA
$ y_{fs} $	forward transfer admittance					
	BF861A		12	-	20	mS
	BF861B		16	-	25	mS
	BF861C		20	-	30	mS
$g_{os}$	common source output conductance					
	BF861A		-	-	200	$\mu\text{S}$
	BF861B		-	-	250	$\mu\text{S}$
	BF861C		-	-	300	$\mu\text{S}$
$C_{iss}$	input capacitance	$f = 1\ \text{MHz}$	-	-	10	pF
$C_{rss}$	reverse transfer capacitance	$f = 1\ \text{MHz}$	-	2.1	2.7	pF
$V_n/\sqrt{B}$	equivalent input noise voltage	$V_{GS} = 0$ ; $f = 1\ \text{MHz}$	-	1.5	-	$\text{nV}/\sqrt{\text{Hz}}$





N-channel junction FETs

BF861A; BF861B; BF861C







N-channel junction FETs

BF861A; BF861B; BF861C







N-channel junction FETs

BF861A; BF861B; BF861C




N-channel junction FETs

BF861A; BF861B; BF861C



N-channel junction FETs


BF861A; BF861B; BF861C



N-channel junction FETs

BF861A; BF861B; BF861C

PACKAGE OUTLINE



Dimensions in mm.

Fig.20 SOT23.

## N-channel junction FETs

## BF861A; BF861B; BF861C

**DEFINITIONS**

<b>Data Sheet Status</b>	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
<b>Limiting values</b>	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
<b>Application information</b>	
Where application information is given, it is advisory and does not form part of the specification.	

**LIFE SUPPORT APPLICATIONS**

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.