



FAST SWITCHING POWER TRANSISTOR

- FAST SWITCHING TIMES
- LOW SWITCHING LOSSES
- VERY LOW SATURATION VOLTAGE AND HIGH GAIN FOR REDUCED LOAD OPERATION



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CEV}	Collector-emitter Voltage ($V_{BE} = -1.5$ V)	300	V
V_{CEO}	Collector-emitter Voltage ($I_B = 0$)	200	V
V_{EBO}	Emitter-base Voltage ($I_C = 0$)	7	V
I_C	Collector Current	20	A
I_{CM}	Collector Peak Current	28	A
I_B	Base Current	4	A
I_{BM}	Base Peak Current	7	A
P_{base}	Reverse Bias Base Dissipation (B.E. junction in avalanche)	1	W
P_{tot}	Total Dissipation at $T_c < 25^\circ\text{C}$	150	W
T_{stg}	Storage Temperature	-65 to 200	°C
T_j	Max. Operating Junction Temperature	200	°C

THERMAL DATA

$R_{th(j-case)}$	Thermal Resistance Junction-case	max	1.17	$^{\circ}\text{C/W}$
------------------	----------------------------------	-----	------	----------------------

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
I_{CER}	Collector Cutoff Current ($R_{BE} = 10\Omega$)	$V_{CE} = V_{CEV}$ $V_{CE} = V_{CEV} \quad T_c = 100^{\circ}\text{C}$			0.5 2.5	mA mA	
I_{CEV}	Collector Cutoff Current	$V_{CE} = V_{CEV} \quad V_{BE} = -1.5\text{V}$ $V_{CE} = V_{CEV} \quad V_{BE} = -1.5\text{V} \quad T_c = 100^{\circ}\text{C}$			0.5 2	mA mA	
I_{EBO}	Emitter Cutoff Current ($I_c = 0$)	$V_{EB} = 5\text{V}$			1	mA	
$V_{CEO(sus)}^*$	Collector Emitter Sustaining Voltage	$I_c = 0.2\text{A}$ $L = 25\text{mH}$	200			V	
V_{EBO}	Emitter-base Voltage ($I_c = 0$)	$I_E = 50\text{mA}$	7			V	
$V_{CE(sat)}^*$	Collector-emitter Saturation Voltage	$I_c = 5\text{A} \quad I_B = 0.25\text{A}$ $I_c = 10\text{A} \quad I_B = 1\text{A}$ $I_c = 14\text{A} \quad I_B = 1.75\text{A}$ $I_c = 5\text{A} \quad I_B = 0.25\text{A} \quad T_j = 100^{\circ}\text{C}$ $I_c = 10\text{A} \quad I_B = 1\text{A} \quad T_j = 100^{\circ}\text{C}$ $I_c = 14\text{A} \quad I_B = 1.75\text{A} \quad T_j = 100^{\circ}\text{C}$		0.4 0.45 0.68 0.4 0.6 0.9	0.8 0.9 1.2 0.9 1.5 1.9	V V V V V V	
$V_{BE(sat)}^*$	Base-emitter Saturation Voltage	$I_c = 10\text{A} \quad I_B = 1\text{A}$ $I_c = 14\text{A} \quad I_S = 1.75\text{A}$ $I_c = 10\text{A} \quad I_B = 1\text{A} \quad T_j = 100^{\circ}\text{C}$ $I_c = 14\text{A} \quad I_B = 1.75\text{A} \quad T_j = 100^{\circ}\text{C}$		1.1 1.3 1 1.2	1.4 1.7 1.4 1.7	V V V V	
dI_c/dt	Rated of Rise of on-state Collector Current	$V_{CC} = 160\text{V} \quad R_C = 0$ See fig. 2	$I_{B1} = 1.5\text{A}$ $T_j = 25^{\circ}\text{C}$ $T_j = 100^{\circ}\text{C}$	35 30	75 65		A/ μ s A/ μ s
$V_{CE(2\mu s)}$	Collector Emitter Dynamic Voltage	$V_{CC} = 160\text{V}$ $R_C = 16\Omega$ See fig. 2	$I_{B1} = 1\text{A}$ $T_j = 25^{\circ}\text{C}$ $T_j = 100^{\circ}\text{C}$		1.8 3	3 5	V V
$V_{CE(4\mu s)}$	Collector Emitter Dynamic Voltage	$V_{CC} = 160\text{V}$ $R_C = 16\Omega$ See fig. 2	$I_{B1} = 1\text{A}$ $T_j = 25^{\circ}\text{C}$ $T_j = 100^{\circ}\text{C}$		1.1 1.4	1.7 2.5	V V

ELECTRICAL CHARACTERISTICS (continued)**RESISTIVE LOAD**

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
t_r	Rise Time	$V_{CC} = 160V$	$I_C = 14A$		0.3	0.6	μs
t_s	Storage Time	$V_{BB} = -5V$	$I_{S1} = 1.7A$		0.6	1.4	μs
t_f	Fall Time	$R_{B2} = 1.4\Omega$	$t_p = 30\mu s$		0.12	0.3	μs
		See fig. 1					

INDUCTIVE LOAD

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
t_s	Storage Time	$V_{CC} = 160V$	$V_{clamp} = 200V$		0.7	1.5	μs
t_f	Fall Time	$I_C = 10A$	$I_B = 1A$		0.06	0.2	μs
t_t	Tail Time in Turn-on	$V_{BB} = -5V$	$R_{B2} = 2.5\Omega$		0.01	0.07	μs
t_c	Crossover Time	$L_C = 0.8mH$	See fig. 3		0.13	0.3	μs
t_s	Storage Time	$V_{CC} = 160V$	$V_{clamp} = 200V$		1.1	2	μs
t_f	Fall Time	$I_C = 10A$	$I_B = 1A$		0.12	0.3	μs
t_t	Tail Time in Turn-on	$V_{BB} = -5V$	$R_{B2} = 2.5\Omega$		0.03	0.15	μs
t_c	Crossover Time	$L_C = 0.8mH$	$T_J = 100^\circ C$		0.24	0.5	μs
t_s	Storage Time	$V_{CC} = 160V$	$V_{clamp} = 200V$		1.5		μs
t_f	Fall Time	$I_C = 10A$	$I_B = 1A$		0.5		μs
t_t	Tail Time in Turn-on	$V_{BB} = 0$	$R_{B2} = 4.7\Omega$		0.12		μs
		$L_C = 0.8mH$	See fig. 3				
t_s	Storage Time	$V_{CC} = 160V$	$V_{clamp} = 200V$		2.7		μs
t_f	Fall Time	$I_C = 10A$	$I_B = 1A$		0.85		μs
t_t	Tail Time in Turn-on	$V_{BB} = 0$	$R_{B2} = 4.7\Omega$		0.25		μs
		$L_C = 0.8mH$	$T_J = 100^\circ C$				

* Pulsed : Pulse duration = 300 μs , duty cycle = 2 %.

Figure 1 : Switching Times Test Circuit (resistive load).









Figure 2 : Turn-on Switching Waveforms.**Figure 3a : Turn-off Switching Test Circuit.****Figure 3b : Turn-off Switching Waveforms (inductive load).**



DC and AC Pulse Area.




Transient Thermal Response.




DC Current Gain.

Power and $I_{S/B}$ Derating versus Case Temperature.


Collector-emitter Voltage versus Base-emitter Resistance.




Minimum Base Current to saturate the Transistor.




Saturation Voltage.




Saturation Voltage.




Switching Times versus Collector Current (resistive load).




Switching Times versus Collector Current (inductive load).



Switching Times versus Collector Current (inductive load).




SWITCHING OPERATING AND OVERLOAD AREAS



Transistor Forward Biased


- During the turn-on
- During the turn-off without negative base-emitter voltage and $4.7\Omega \leq R_{BE} \leq 50\Omega$



Transistor Reverse Biased


- During the turn-off with negative base-emitter voltage

Forward Biased Safe Operating Area (FBSOA).



The hatched zone can only be used for turn-on.


Forward Biased Accidental Overload Area (FBAOA).




The Kellogg network (heavy point) allows the calculation of the maximum value of the short-circuit for a given base current I_B (90 % confidence).

High accidental surge currents ($I > I_{CM}$) are allowed if they are non repetitive and applied less than 3000 times during the component life.

Reverse Biased Safe Operating Area (RBSOA).



Reverse Biased Accidental Overload Area (RBAOA).



After the accidental overload current the RBAOA has to be used for the turn-off.