



PNP LOW VOLTAGE TRANSISTOR

PRELIMINARY DATA

- LOW COLLECTOR SATURATION VOLTAGE
- EXCELLENT LINEARITY



INTERNAL SCHEMATIC DIAGRAM



DESCRIPTION

The D45H1, D45H2, D45H4, D45H5, D45H7, D45H8 and D45H10 are silicon multiepitaxial planar PNP transistors in TO-220 plastic package, intended for switching and general purpose applications.

The complementary NPN types are the D44H1, D44H2, D44H4, D44H5, D44H7, D44H8 and D44H10 respectively.

ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | | | | Unit |
|-----------|---|----------------|----------------|----------------|--------|------|
| | | D45H1 D45H2 | D45H4 D45H5 | D45H7 D45H8 | D45H10 | |
| V_{CBO} | Collector-base Voltage ($I_E = 0$) | - 30 | - 45 | - 60 | - 80 | V |
| V_{CEO} | Collector-emitter Voltage ($I_B = 0$) | - 30 | - 45 | - 60 | - 80 | V |
| V_{EBO} | Emitter-base Voltage ($I_C = 0$) | | | - 5 | | V |
| I_C | Collector Current | | | - 10 | | A |
| I_{CM} | Collector Peak Current | | | - 20 | | A |
| I_B | Base Current | | | - 5 | | mA |
| P_{tot} | Total Dissipation at $T_c < 25^\circ\text{C}$ | | | 50 | | W |
| T_{stg} | Storage Temperature | | | - 55 to 150 | | °C |
| T_j | Max. Operating Junction Temperature | | | 150 | | °C |

THERMAL DATA

| | | | | |
|-----------------------|----------------------------------|-----|-----|----------------------|
| $R_{\text{thj-case}}$ | Thermal Resistance Junction-case | max | 2.5 | $^{\circ}\text{C/W}$ |
|-----------------------|----------------------------------|-----|-----|----------------------|

ELECTRICAL CHARACTERISTICS ($T_{\text{case}} = 25^{\circ}\text{C}$ unless otherwise specified)

| Symbol | Parameter | Test Conditions | | Min. | Typ. | Max. | Unit |
|-------------------------|--|--|---|--------------------------|-----------|----------|---------------|
| I_{CBO} | Collector Cutoff Current ($I_E = 0$) | $V_{\text{CB}} = -30\text{V}$ | for D45H1/2 | | | -10 | μA |
| | | $V_{\text{CB}} = -45\text{V}$ | for D45H4/5 | | | -10 | μA |
| | | $V_{\text{CB}} = -60\text{V}$ | for D45H7/8 | | | -10 | μA |
| | | $V_{\text{CB}} = -80\text{V}$ | for D45H10 | | | -10 | μA |
| I_{EBO} | Emitter Cutoff Current ($I_C = 0$) | $V_{\text{EB}} = -5\text{V}$ | | | | -0.1 | mA |
| $V_{\text{CEO(sus)}}^*$ | Collector-emitter Sustaining Voltage | $I_C = -0.1\text{A}$ | for D45H1/2 for D45H4/5 for D45H7/8 for D45H10 | -30 -45 -60 -80 | | | V |
| $V_{\text{CE(sat)}}^*$ | Collector-emitter Saturation Voltage | $I_C = -8\text{A} \quad I_B = -0.4\text{A}$ $I_C = -8\text{A} \quad I_B = -0.8\text{A}$ | for D45H2/5/8 for D45H1/4/7/10 | | | -1 -1 | V |
| $V_{\text{BE(sat)}}^*$ | Base-emitter Saturation Voltage | $I_C = -8\text{A} \quad I_B = -0.8\text{A}$ | | | | -1.5 | V |
| h_{FE}^* | DC Current Gain | $I_C = -2\text{A} \quad V_{\text{CE}} = -1\text{V}$ $I_C = -4\text{A} \quad V_{\text{CE}} = -1\text{V}$ | for D45H2/5/8 for D45H1/4/7/10 | 60 35 | 120 60 | | |
| | | | | | | 40 20 | 70 50 |

* Pulsed : Pulse duration = 300 μs , duty cycle = 1.5%.