


Digital transistor (built-in resistor)

DTB114TK

●Features

- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors.
- The bias resistors consist of thin-film resistors with complete isolation to allow positive biasing of the input, and parasitic effects are almost completely eliminated.
- Only the on/off conditions need to be set for operation, making device design easy.
- Higher mounting densities can be achieved.

●Circuit schematic**●Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV _{CBO}	-50	—	—	V	I _C =-50 μA
Collector-emitter breakdown voltage	BV _{CEO}	-40	—	—	V	I _C =-1mA
Emitter-base breakdown voltage	BV _{EBO}	-5	—	—	V	I _E =-50 μA
Collector cutoff current	I _{CEO}	—	—	-0.5	μA	V _{CB} =-50V
Emitter cutoff current	I _{EBO}	—	—	-0.5	μA	V _{SB} =-4V
Collector-emitter saturation voltage	V _{CE(sat)}	—	—	-0.3	V	I _C /I _E =-50mA/-2.5mA
DC current transfer ratio	h _{FE}	100	250	600	—	I _C =-50mA, V _{CE} =-5V
Input resistance	R ₁	7	10	13	kΩ	—
Transition frequency	f _T	—	200	—	MHz	V _{CE} =-10V, I _E =5mA, f=100MHz

* Transition frequency of the device.

(96-294-B114T)

Digital transistor (built in resistors and zener diode), driver (60V, 1A)


DTDG23YP

●Features

- High DC current gain. (Min. 300 at V_O/I_O=2V/0.5A)
- Low output voltage. (Typ. 0.4V at I_O/I_I=500/50mA)
- Built-in zener diode gives strong protection against reverse

●Structure

NPN digital transistor
(with built in resistors and zener diode)

●Circuit schematic**●Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Input voltage	V _{I(off)}	—	—	0.3	V	V _{CC} =5V, I _O =100 μA
V _{I(on)}	2	—	—	—	—	V _O =0.4V, I _O =100mA
Output voltage	V _{O(on)}	—	—	0.4	V	I _O /I _I =500mA/5mA
Input current	I _I	—	—	3.6	mA	V _I =5V
Output current	I _{O(off)}	—	—	0.5	μA	V _{CC} =40V, V _I =0V
DC current gain	G _I	300	—	—	—	V _O =2V, I _O =500mA
Transition frequency	f _T	—	80	—	MHz	V _{CE} =5V, I _E =-0.1A, f=30MHz
Input resistance	R ₁	1.54	2.2	2.86	kΩ	—
Emitter-base resistance	R ₂	7	10	13	kΩ	—

* Transition frequency of the device.

(96-378-DS23YP)