

**N - CHANNEL ENHANCEMENT MODE  
POWER MOS TRANSISTORS**

PRELIMINARY DATA

TYPE	V <sub>DSS</sub>	R <sub>DS(on)</sub>	I <sub>D</sub> ■
IRF530	100 V	0.16 Ω	14 A
IRF530FI	100 V	0.16 Ω	9 A
IRF531	80 V	0.16 Ω	14 A
IRF531FI	80 V	0.16 Ω	9 A
IRF532	100 V	0.23 Ω	12 A
IRF532FI	100 V	0.23 Ω	8 A
IRF533	80 V	0.23 Ω	12 A
IRF533FI	80 V	0.23 Ω	8 A

- 80-100 VOLTS - FOR DC/DC CONVERTERS
- HIGH CURRENT
- ULTRA FAST SWITCHING
- EASY DRIVE- FOR REDUCED COST AND SIZE

**INDUSTRIAL APPLICATIONS:**

- UNINTERRUPTIBLE POWER SUPPLIES
- MOTOR CONTROLS

N - channel enhancement mode POWER MOS field effect transistors. Easy drive and very fast switching times make these POWER MOS transistors ideal for high speed switching applications. Applications include DC/DC converters, UPS, battery chargers, secondary regulators, servo control, power-audio amplifiers and robotics.

**ABSOLUTE MAXIMUM RATINGS**


 TO-220  
 ISOWATT220

	TO-220	IRF			
		530	531	532	533
	ISOWATT220	530FI	531FI	532FI	533FI
V <sub>DS</sub> *	Drain-source voltage (V <sub>GS</sub> = 0)	100	80	100	80
V <sub>DGR</sub> *	Drain-gate voltage (R <sub>GS</sub> = 20 kΩ)	100	80	100	80
V <sub>GS</sub>	Gate-source voltage			±20	
I <sub>DM</sub> (•)	Drain current (pulsed)	56	56	48	48
I <sub>DLM</sub>	Drain inductive current, clamped (L = 100 μH)	56	56	48	48
I <sub>D</sub>	Drain current (cont.) at T <sub>c</sub> = 25°C	530	531	532	533
I <sub>D</sub>	Drain current (cont.) at T <sub>c</sub> = 100°C	14	14	12	12
I <sub>D</sub> ■	Drain current (cont.) at T <sub>c</sub> = 25°C	9	9	8	8
I <sub>D</sub> ■	Drain current (cont.) at T <sub>c</sub> = 100°C	5.5	5.5	5	5
P <sub>tot</sub> ■	Total dissipation at T <sub>c</sub> < 25°C	79	35		
■	Derating factor	0.63	0.28		
T <sub>stg</sub>	Storage temperature	-55 to 150			
T <sub>j</sub>	Max. operating junction temperature	150			


 \* T<sub>c</sub> = 25°C to 125°C

(•) Repetitive Rating: Pulse width limited by max junction temperature.

■ See note on ISOWATT220 on this datasheet.



ISOWATT220

**INTERNAL SCHEMATIC  
DIAGRAM**


## THERMAL DATA

TO-220 | ISOWATT220

$R_{thj\text{-case}}$	Thermal resistance junction-case	max	1.58	3.57	$^{\circ}\text{C/W}$
$R_{thc\text{-s}}$	Thermal resistance case-sink	typ	0.5	$^{\circ}\text{C/W}$	
$R_{thj\text{-amb}}$	Thermal resistance junction-ambient	max	80	$^{\circ}\text{C/W}$	
$T_f$	Maximum lead temperature for soldering purpose		300	$^{\circ}\text{C}$	

ELECTRICAL CHARACTERISTICS ( $T_{\text{case}} = 25^{\circ}\text{C}$  unless otherwise specified)

Parameters	Test Conditions	Min.	Typ.	Max.	Unit
------------	-----------------	------	------	------	------

## OFF

$V_{(\text{BR})\text{DSS}}$	Drain-source breakdown voltage	$I_D = 250 \mu\text{A}$ for IRF530/532/530FI/532FI for IRF531/533/531FI/533FI	$V_{GS} = 0$	100		V
100		80				V
$I_{\text{DSS}}$	Zero gate voltage drain current ( $V_{GS} = 0$ )	$V_{DS} = \text{Max Rating}$ $V_{DS} = \text{Max Rating} \times 0.8$	$T_c = 125^{\circ}\text{C}$	250	$\mu\text{A}$	$\mu\text{A}$
1000				1000		
$I_{\text{GSS}}$	Gate-body leakage current ( $V_{DS} = 0$ )	$V_{GS} = \pm 20 \text{ V}$			$\pm 100$	nA

## ON \*\*

$V_{GS\text{(th)}}$	Gate threshold voltage	$V_{DS} = V_{GS}$	$I_D = 250 \mu\text{A}$	2		V
$I_{D\text{(on)}}$	On-state drain current	$V_{DS} > I_{D\text{(on)}} \times R_{DS\text{(on) max}}$ for IRF530/531/530FI/531FI for IRF532/533/532FI/533FI	$V_{GS} = 10 \text{ V}$	14		A
$R_{DS\text{(on)}}$	Static drain-source on resistance	$V_{GS} = 10 \text{ V}$ for IRF530/531/530FI/531FI for IRF532/533/532FI/533FI	$I_D = 8.3 \text{ A}$	12		A
				0.16		$\Omega$
				0.23		$\Omega$

## DYNAMIC

$g_{fs}^{**}$	Forward transconductance	$V_{DS} > I_{D\text{(on)}} \times R_{DS\text{(on) max}}$ $I_D = 8.3 \text{ A}$	5.1		mho
$C_{iss}$	Input capacitance				
$C_{oss}$	Output capacitance				
$C_{rss}$	Reverse transfer capacitance				
				850	pF
				260	pF
				50	pF

## SWITCHING

$t_d\text{(on)}$	Turn-on time	$V_{DD} = 36 \text{ V}$	$I_D = 8.0 \text{ A}$	30	ns
$t_r$	Rise time	$R_j = 15 \Omega$		75	ns
$t_d\text{(off)}$	Turn-off delay time		(see test circuit)	40	ns
$t_f$	Fall time			45	ns
$Q_g$	Total Gate Charge	$V_{GS} = 10 \text{ V}$	$I_D = 14 \text{ A}$	30	nC
		$V_{DS} = \text{Max Rating} \times 0.8$			
		(see test circuit)			

## ELECTRICAL CHARACTERISTICS (Continued)

Parameters	Test Conditions	Min.	Typ.	Max.	Unit
------------	-----------------	------	------	------	------

## SOURCE DRAIN DIODE

$I_{SD}$	Source-drain current				14	A
$I_{SD}^*$	Source-drain current (pulsed)				56	A
$V_{SD}^{**}$	Forward on voltage	$I_{SD} = 14 \text{ A}$	$V_{GS} = 0$		2.5	V
$t_{rr}$	Reverse recovery time	$T_j = 150^\circ\text{C}$		360		ns
$Q_{rr}$	Reverse recovered charge	$I_{SD} = 14 \text{ A}$	$dI/dt = 100 \text{ A}/\mu\text{s}$	21		$\mu\text{C}$

\*\* Pulsed: Pulse duration  $\leq 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ 

(\*) Repetitive Rating: Pulse width limited by max junction temperature

■ See note on ISOWATT220 in this datasheet

► SOURCE DRAIN FOR DC-DC CONVERTERS

► HIGH CURRENT

## ISOWATT220 PACKAGE CHARACTERISTICS AND APPLICATION.

ISOWATT220 is fully isolated to 2000V dc. Its thermal impedance, given in the data sheet, is optimised to give efficient thermal conduction together with excellent electrical isolation.

The structure of the case ensures optimum distances between the pins and heatsink. The ISOWATT220 package eliminates the need for external isolation so reducing fixing hardware. Accurate moulding techniques used in manufacture assure consistent heat spreader-to-heatsink capacitance.

ISOWATT220 thermal performance is better than that of the standard part, mounted with a 0.1mm mica washer. The thermally conductive plastic has a higher breakdown rating and is less fragile than mica or plastic sheets. Power derating for ISOWATT220 packages is determined by:

$$P_D = \frac{T_j - T_c}{R_{th}}$$

from this  $I_{Dmax}$  for the POWER MOS can be calculated:

$$I_{Dmax} \leq \sqrt{\frac{P_D}{R_{DS(on)} (\text{at } 150^\circ\text{C})}}$$

## THERMAL IMPEDANCE OF ISOWATT220 PACKAGE

Fig. 1 illustrates the elements contributing to the thermal resistance of transistor heatsink assembly, using ISOWATT220 package.

The total thermal resistance  $R_{th(\text{tot})}$  is the sum of each of these elements.

The transient thermal impedance,  $Z_{th}$  for different pulse durations can be estimated as follows:

1 - for a short duration power pulse less than 1ms;

$$Z_{th} < R_{thJ-C}$$

2 - for an intermediate power pulse of 5ms to 50ms:

$$Z_{th} = R_{thJ-C}$$

3 - for long power pulses of the order of 500ms or greater:

$$Z_{th} = R_{thJ-C} + R_{thC-HS} + R_{thHS-amb}$$

It is often possible to discern these areas on transient thermal impedance curves.

Fig. 1

