

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

2N3641 PN3641
2N3642 PN3642
2N3643 PN3643

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960

JEDEC TO-105 JEDEC TO-92

NPN SILICON SIGNAL TRANSISTORS

MAXIMUM RATINGS (TA=25°C)

	<u>SYMBOL</u>	<u>2N3641</u> <u>PN3641</u>	<u>2N3642</u> <u>PN3642</u>	<u>UNIT</u>
Collector-Base Voltage	V _{CBO}	60	60	V
Collector-Emitter Voltage	V _{CEO}	30	45	V
Emitter-Base Voltage	V _{EBO}	5.0	5.0	V
Collector Current	I _C	500	500	mA
		<u>2N3641</u> <u>2N3642</u> <u>2N3643</u>	<u>PN3641</u> <u>PN3642</u> <u>PN4643</u>	
Power Dissipation	P _D	350	625	mW
Operating and Storage Junction Temperature	T _J , T _{Stg}	-55 TO +125	-55 TO +150	°C

ELECTRICAL CHARACTERISTICS (TA=25°C)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>2N3641</u> <u>PN3641</u>		<u>2N3642</u> <u>PN3642</u>		<u>2N3643</u> <u>PN3643</u>		<u>UNIT</u>
		<u>MIN</u>	<u>MAX</u>	<u>MIN</u>	<u>MAX</u>	<u>MIN</u>	<u>MAX</u>	
I _{CES}	V _{CE} =50V			50	50	50	50	nA
BV _{CBO}	I _C =10µA	60	60	60	60	60	60	V
BV _{CES}	I _C =10µA	60	60	60	60	60	60	V
BV _{CEO}	I _C =10mA	30	45	30	45	30	45	V
BV _{EBO}	I _E =10µA	5.0	5.0	5.0	5.0	5.0	5.0	V
V _{CE} (SAT)	I _C =150mA, I _B =15mA			0.22	0.22	0.22	0.22	V
h _{FE}	V _{CE} =10V, I _C =150mA	40	120	40	120	100	300	
h _{FE}	V _{CE} =10V, I _C =500mA	15	15	15	15	25	25	
f _T	V _{CE} =5.0V, I _C =50mA, f=100MHz	150	150	150	150	250	250	MHz
C _{ob}	V _{CB} =10V, f=140kHz			8.0	8.0	8.0	8.0	pF
G _{pe}	V _{CE} =15V, R _G =140Ω, R _L =260Ω, f=30MHz, P _{IN} =40mW	10	10	10	10	10	10	dB
η	V _{CE} =15V, R _G =140Ω, R _L =260Ω, f=30MHz, P _{IN} =40mW	60	60	60	60	60	60	%
t _{on}	I _C =300mA, I _{B1} =30mA			60	60	60	60	ns
t _{off}	I _C =300mA, I _{B1} =I _{B2} =30mA			150	150	150	150	ns

NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

