

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

TIP30
TIP30A
TIP30B
TIP30C

SILICON PNP POWER TRANSISTOR
1 AMP, 30 WATTS

JEDEC TO-220 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR TIP30 Series is a PNP Epitaxial-Base Silicon Power Transistor designed for power amplifier and high-speed switching applications.

MAXIMUM RATINGS (T_C=25°C unless otherwise noted)

	SYMBOL	TIP30	TIP30A	TIP30B	TIP30C	UNIT
Collector-Base Voltage	V _{CB0}	40	60	80	100	V
Emitter-Base Voltage	V _{EB0}	5.0	5.0	5.0	5.0	V
Collector-Emitter Voltage	V _{CE0}	40	60	80	100	V
Collector Current, Continuous	I _C	1.0	1.0	1.0	1.0	A
Collector Current, Peak	I _{CM}	3.0	3.0	3.0	3.0	A
Base Current	I _B	0.4	0.4	0.4	0.4	A
Power Dissipation	P _D	30	30	30	30	W
Power Dissipation (T _A =25°C)	P _D	2.0	2.0	2.0	2.0	W
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 TO +150		-65 TO +150		°C

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I _{CE0}	V _{CE} =30V (TIP30, TIP30A)		0.3	mA
I _{CE0}	V _{CE} =60V (TIP30B, TIP30C)		0.3	mA
I _{CES}	V _{CE} =Rated V _{CE0}		0.2	mA
I _{EB0}	V _{EB} =5.0V		1.0	mA
BV _{CE0}	I _C =30mA, (TIP30)	40		V
BV _{CE0}	I _C =30mA, (TIP30A)	60		V
BV _{CE0}	I _C =30mA, (TIP30B)	80		V
BV _{CE0}	I _C =30mA, (TIP30C)	100		V
V _{CE(SAT)}	I _C =1.0A, I _B =125mA		0.7	V
V _{BE(on)}	V _{CE} =4.0V, I _C =1.0A		1.3	V
h _{FE}	V _{CE} =4.0V, I _C =0.2A	40		-
h _{FE}	V _{CE} =4.0V, I _C =1.0A	15	75	-
h _{fe}	V _{CE} =10V, I _C =0.2A, f=1 kHz	20		-
f _T	V _{CE} =10V, I _C =0.2A, f=1 MHz	3		MHz
t _{on}	I _C =1.0A, I _{B1} =I _{B2} =100mA, R _L =30 OHMS	0.3 TYP		µSEC
t _{off}	I _C =1.0A, I _{B1} =I _{B2} =100mA, R _L =30 OHMS	1.0 TYP		µSEC